TECHNICAL REPORT ARLCD-TR-84026

DESIGN OF AMMUNITION GRIPPER FOR 155-MM ROBOTIC HOWITZER

ROBERT M. NITZSCHE

MARCH 1985

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER

LARGE CALIBER WEAPON SYSTEMS LABORATORY

DOVER, NEW JERSEY

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER Technical Report ARLCD-TR-84026	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE *(and Subtitle)* DESIGN OF AMMUNITION GRIPPER FOR 155-mm ROBOTIC HOWITZER		5. TYPE OF REPORT & PERIOD COVERED May – September 1983
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Robert M. Nitzsche		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS ARDC, LCWSL Weapons Div (SMCAR-LCW-E) Dover, NJ 07801-5001		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS ARDC, TSD STINFO Div (SMCAR-TSS) Dover, NJ 07801-5001		12. REPORT DATE March 1985
		13. NUMBER OF PAGES 109
14. MONITORING AGENCY NAME & ADDRESS*(if different from Controlling Office)*		15. SECURITY CLASS. *(of this report)* Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT *(of this Report)*

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT *(of the abstract entered in Block 20, if different from Report)*

18. SUPPLEMENTARY NOTES

19. KEY WORDS *(Continue on reverse side if necessary and identify by block number)*

Gripper	Ammunition handling	155-mm howitzer
End effector	Integrated Smart Artillery Synthesis	
End-of-arm tooling	Design	ISAS
Robotic	Hydraulic	
Artillery	155-mm projectiles	

20. ABSTRACT *(Continue on reverse side if necessary and identify by block number)*

A robotic gripper which picks up 155-mm projectiles and cylindrical propelling charges and holds them securely while they are moved through any orientation within a self-propelled howitzer is described. The exact tasks that the gripper must perform are studied and four preliminary concepts are shown. One concept is developed. The development effort includes a kinematic analysis, force analysis, stress analysis, and a complete drawing package.

CONTENTS

FIGURES

INTRODUCTION

This report describes the development of a robotic gripper. Its function is to grasp and securely hold 6-inch-diameter (155-mm) projectiles and 6.25-inch-diameter modular propelling charges longitudinally about their center of gravity as they are moved through any orientation.

The gripper and its robotic arm are part of the Integrated Smart Artillery Synthesis (ISAS) project presently under development and will be installed in a modified M109 self-propelled howitzer (fig. 1). The robot transports the projectiles and charges from different locations within the howitzer and places them on an autoloader tray.

Most robotic systems which transport heavy loads keep them in an orientation parallel to the plane of the earth while permitting movement perpendicular to that plane (fig. 2). Several types of grippers are used to accomplish this task. One uses magnetic force; another employs pneumatic suction; a third utilizes mechanical force. A mechanical gripper may be hydraulically, pneumatically, or electrically powered.

Occasionally heavy loads must be moved through a variety of orientations. Generally, such loads are supported by bracing as shown in figure 3. Bracing permits rotation of up to 180 degrees out of a fixed plane of motion. An alternative method is to mechanically grasp the load with sufficient force to hold it securely in any plane. A third method makes use of a fixed frame containing an inflatable seal. When the seal is expanded, hydrostatic pressure holds the load in place.

DESIGN SPECIFICATIONS

There are numerous specifications which the gripper must meet. For example, it must operate in a temperature range of 0 to 125°F. It must be weatherproof, but not necessarily waterproof. It must also be capable of operating in environments containing high levels of dust and dirt.

The maximum size of the gripper is determined by the space envelope available. The projectile rack configuration is such that a gripper may not be more than 9 inches wide. The gripper will partially encircle a projectile at its center of gravity in the area between the rotating bands and the bourrelet (fig. 4). The length of the gripper (distance from the outer edge of one finger to the outer edge of the other) may not exceed 8 inches.

For determining the gripper's height profile, the working area can be divided into two parts; that above the centerline of the projectile and that below the centerline. Dimensions above the centerline of the projectile are governed by the configuration of the robot. A representation of the robot in its flexed position holding a projectile is shown in figure 4. The gripper illustrated is an early concept. The projectile's centerline must be approximately 15

inches below the robot's lower joint to avoid interference. The design parameter is such that the gripper must fit between the middle section of the robot arm and the projectile when the robot is in this configuration.

The gripper will weigh approximately 30 pounds. It will be hydraulically powered by a system developing 2,000 psi operating pressure. The gripper must have sufficient holding force to permit transporting projectiles and charges in any attitude. The length of the robot arm may not exceed 43 inches. The robot's rotating joints will have a maximum angular velocity of 90 degrees per second. The x-y gantry to which the robot is attached will have a maximum traversing speed of 15 inches per second in both the x and y directions. The robot must be capable of stopping in 0.1 second. These specifications are used to calculate holding force requirements.

The gripper must also contain a feature which will operate a latch to release projectiles and charges from their racks. The exact psoition of the latches on the racks will be determined during the gripper's final design.

GRIPPER CONCEPTS

Prior to development of the gripper concepts, known types were studied. Magnetic grippers were ruled out because the propelling charges they would be transporting are nonmagnetic. Pneumatic grippers were rejected because the available power source is hydraulic. A product search was conducted but no suitable gripper was found. Results of this investigation are described in appendix A.

In view of the nonavailability of a commercial product, an in-house concept study was initiated. Four design approaches were used.

The first design is shown in figure 5. This gripper consists of two U-shaped members, each containing three pistons. After the gripper is placed around the load, hydraulic pressure is applied to the pistons. The relative displacement of each piston is then measured and the robot automatically corrects its position to center the load. Once the load is centered, two valves are automatically closed to fix each piston in position. The accuracy of the robot when grasping its load is not critical because the gripper contains a positioning feedback system. This concept is easy to maintain since the readily accessible pistons are its only repair parts.

There are, however, disadvantages to this design. The position sensors required for the feedback system are costly. The pressure exerted upon the projectiles and charges is high, since the contact area is small. The gripper's required thickness, as determined by piston expansion, would probably exceed the desired space envelope. Also, in this application the force reactions on each piston are unusual in that they are not parallel to the piston's stroke. Therefore, the pistons will probably not be available as off-the-shelf items.

The second concept is shown in figure 6. This configuration is similar to the first concept but uses hydraulically inflatable gaskets in lieu of pistons. In this application, the shape of the gaskets is critical. If not properly shaped, they will permit the load to shift downward. When this occurs, fluid will flow through the gaskets causing them to expand above the centerline of the load. This will result in dropping the load. Presray Corporation fabricates inflatable gaskets which are capable of exerting the required force. They are also compatible with MIL-H-6083 hydraulic fluid. These gaskets, however, do not possess the shear strength required to hold the load.

The third concept, shown in figure 7, was devised following a study of available hydraulic actuators. Because hydraulics are usually associated with large items, most off-the-shelf actuators are too big or too heavy. However, Bimba Manufacturing Company makes a hydraulic cylinder 0.625 inch in diameter and 5 inches long with a 4-inch stroke. In this concept, when the cylinder is actuated, link two slides along the ground link, closing link three. As in the previous concepts, two gripper assemblies are required. This mechanism's greatest attribute is that it uses an off-the-shelf actuator; however, it requires a large space envelope.

The fourth concept evolved from the third concept. It was recognized that if link two of the third concept (fig. 7) were reshaped and driven from the sliding point, it would result in a more compact, efficient design. This fourth concept (fig. 8) requires the use of a different type actuator. A rotary actuator driving a cam was evaluated and discarded as being too heavy. However, the mechanism could also be driven by a linear actuator. Research has revealed that Fabco-Air, Inc. manufactures such an actuator. This company offers a line of pneumatic short-stroke "pancake" cylinders which could be used with low pressure hydraulics (under 500 psi nonshock).

Since the fourth concept appeared feasible, it was chosen for development.

GENERAL DESIGN OF DEVELOPED CONCEPT

Of the concepts previously described, the fourth was developed by computer program to determine the link lengths that would fit within the space envelope. The analysis, the program, and the program's output are described in appendix B.

As shown in appendix B, figure B-1, the distance between the center line of the mechanism and the lower left-hand pin (R) was varied from 3.3 inches to 4.5 inches in 0.1-inch increments. The distance between the center pivot point and the low end of the piston's stroke (S) was varied from 0.3-inch to 1.5 inches in 0.1-inch increments. The distance between the center line of the mechanism and the low end of the piston's stroke (D) was varied from 4 inches to 5.3 inches in 0.1-inch increments. The transmission angle (θ) of the closed linkage was fixed at 95 degrees. The initial transmission angle was varied from 121 degrees to 135 degrees in 1-degree increments. The longitudinal distance between the center line of the projectile and lower left-hand (Y) was fixed at 1 inch.

3

It was found that the space claim of this design did not exceed the space envelope. The program checked 35,490 linkages and found 195 desirable linkages.

Trends were studied, layout drawings were prepared, and a new generalized shape was conceived (fig. 9). This gripper appears to meet the design criteria.

GRIPPING FORCE

The gripper must overcome dynamic as well as static loads. These forces may be additive and cause the load to slip from the gripper. Therefore, the normal force (N) produced by the gripper must be sufficient to overcome slipping.

The robot arm's most critical orientation is illustrated in figure 10. In this instance, the robot is stopped while in full swing. The linear impulse, caused by stopping the arm, and the weight of the projectile are additive. (The angular impulse resulting from stopping the rotation of the projectile is comparatively small and is ignored.)

The linear impulse ($\overline{F}_i$) can be approximated by the following relationship:

$$\overline{F}_i = \frac{\overline{V}_i - \overline{V}_o}{t} \frac{W}{g} \tag{1}$$

where

V_i = Initial velocity of projectile (in./sec)

V_o = Final velocity of projectile (in./sec)

W = Weight of projectile (lb)

t = Change in time (sec)

g = Gravitational constant = 386.4 (in./sec^2)

The initial velocity is the cross product of the angular velocity (ω) of the robot arm with the distance (r) between the center of the arm's rotation and the center line of the projectile. Since the impulse force vector and the load vector are in the same direction, vector notation is dropped. When it is known that the maximum angular velocity of the arm is $\pi/2$ rad/sec, and the distance (r) is 48 inches, initial velocity can be calculated as

$$V_i = \omega\, r \tag{2}$$

$$V_i = \left(\frac{\pi}{2}\frac{rad}{sec}\right)(48.0\ in.)$$

$$V_i = 75.4 \text{ in./sec}$$

Since the final ω is zero, V_o is zero. The weight of the heaviest projectile is 103.4 pounds. The robot must stop within 0.1 second. This is the worst-case stop for the robot, so t is assumed to be 0.1 second. The linear impulse can now be calculated by equation 1.

$$F = \frac{(75.4 \text{ in./sec} - 0 \text{ in./sec})(103.4 \text{ lb})}{(0.1 \text{ sec})(386.4 \text{ in./sec}^2)} \tag{3}$$

$$F_i = 201.8 \text{ lb}$$

The total weight (F_T) is the sum of the impulse force and the projectile's weight.

$$F_T = 201.8 \text{ lb} + 103.4 \text{ lb} \tag{4}$$

$$F_T = 305.2 \text{ lb}$$

The friction force (f) between the gripper and the projectile must, as a minimum, equal F_T.

$$f = F_T \tag{5}$$

$$f = 305.2 \text{ lb}$$

When the gripper is holding the projectile, the normal force (N_p) produced must equal the quotient of the friction force (f) and the coefficient of friction between the two surfaces (μ).

$$N_p = \frac{f}{\mu} \tag{6}$$

The coefficient of dynamic friction between steel and paint is approximately 0.35. Since this is the minimum normal force required, a 10% safety factor is used.

$$N_p = \frac{305.2 \text{ lb}}{0.35}(1.1) \tag{7}$$

$$N_p = 959 \text{ lb}$$

The normal force needed to hold the charge (N_c) can be calculated in the same manner. The weight of the charge is 30 pounds, and the coefficient of friction is 0.4. When the same procedure is used, N_c is 243.5 pounds.

In the following sections, the maximum forces and stresses acting upon the components of the gripper are studied. Since N_p is greater than N_c, the computations are based upon the requirements for N_p.

5

FORCE ANALYSIS

The forces acting upon the gripper are greatest when the arm is rotating and the projectile is parallel to the ground. Vector forces added to the minimum normal force required to hold the projectile include the weight of the projectile and the dynamic force from the normal component of the projectile's acceleration. Since the forces resulting from the normal acceleration and the weight of the projectile (W) are in the same direction, vector notation is omitted. The normal acceleration (a_n) can be calculated using the following relation:

$$a_n = \omega^2 r \tag{8}$$

From this, the normal force is calculated.

$$F_n = \frac{a_n W}{g} \tag{9}$$

$$F_n = \frac{\omega^2 r W}{g}$$

$$F_n = \frac{\left(\frac{\pi}{2} \frac{rad}{sec}\right)^2 (48 \text{ in.}) (103.4 \text{ lb})}{(386.4 \text{ in./sec}^2)}$$

$$F_n = 31.7 \text{ lb}$$

The maximum force (FTp) attributable to the projectile is the sum of the dynamic force and its static weight.

$$FTp = F_n + W \tag{10}$$

$$FTp = 31.7 \text{ lb} + 103.4 \text{ lb}$$

$$FTp = 135.1 \text{ lb}$$

The gripper has four fingers, so the additional force (Fe) on each will be one quarter the total added force.

$$Fe = 0.25 \; FTp \tag{11}$$

$$Fe = 0.25 \;(135.1 \text{ lb})$$

$$Fe = 33.8 \text{ lb}$$

The minimum normal force on each finger remains at 959 pounds, since friction is not a function of area (number of fingers). With the layout in figure 11, the maximum normal force (N) is the vector sum of the minimum normal force and the weight of the load.

$$N = Np + Fe \cos 52° \tag{12}$$

$$N = 959 \text{ lb} + 33.8 \text{ lb} \cos 52°$$

$$N = 980 \text{ lb}$$

Each gripper makes 3-point contact with its load. By summing the forces in the y direction, the reaction force (R) can be calculated.

$$\Sigma Fy = 0 \tag{13}$$

$$R + FTp \ (0.5) - 2N \sin 38° = 0$$

$$R = -FTp \ (0.5) + 2N \sin 38°$$

$$R = -135.1 \text{ lb} \ (0.5) + 2 \ (980 \text{ lb}) \sin 38°$$

$$R = 1,139 \text{ lb}$$

The internal forces of the gripper can now be calculated. Starting with the finger (fig. 12), moments can be summed about point C to determine the magnitude of FAB.

$$\Sigma Mc = 0 \tag{14}$$

$$2.387 \text{ in. } FAB \cos 17° - 3.25 \text{ in. } N \cos 38° - 1.7 \text{ in. } N \sin 38° = 0$$

$$FAB = \frac{N \ (3.25 \text{ in. } \cos 38° + 1.7 \text{ in. } \sin 38°)}{2.387 \text{ in. } \cos 17°}$$

$$FAB = \frac{980 \text{ lb } (3.25 \text{ in. } \cos 38° + 1.7 \text{ in. } \sin 38°}{2.387 \text{ in. } \cos 17°}$$

$$FAB = 1,549 \text{ lb}$$

Once FAB is known, Cx, Cy, the magnitude of C, and its direction from the x axis (β), can be determined by summing the forces in the X and Y directions.

$$\Sigma Fx = 0 \tag{15}$$

$$Cx - FAB \cos 17° - N \cos 38° = 0$$

$$Cx = FAB \cos 17° + N \cos 38°$$

$$Cx = 1,549 \text{ lb } \cos 17° + 980 \text{ lb } \cos 38°$$

$$Cx = 2,253 \text{ lb}$$

$$\Sigma Fy = 0 \tag{16}$$

$$Cy - FAB \sin 17° - N \sin 38° = 0$$

$$Cy = FAB \sin 17° + N \sin 38°$$

$$Cy = 1{,}549 \text{ lb} \sin 17° + 980 \text{ lb} \sin 38°$$

$$Cy = 1{,}056 \text{ lb}$$

$$|C| = (Cx^2 + Cy^2)^{1/2} \tag{17}$$

$$|C| = [(2{,}254 \text{ lb})^2 + (1{,}056)^2]^{1/2}$$

$$|C| = 2{,}489 \text{ lb}$$

$$\beta = \tan^{-1} \frac{Cy}{Cx} \tag{18}$$

$$\beta = \tan^{-1} \frac{1{,}056 \text{ lb}}{2{,}253 \text{ lb}}$$

$$\beta = 25°$$

Also, once FAB is known, the forces on the yoke (fig. 13) can be determined. Since there are two forces at the finger connection, each will be one half FAB, or 775 pounds. When the forces along the yoke are summed, FBA must equal FAB in magnitude and be opposite in direction. Since one of the forces at the yoke's finger connection is offset from the other two forces, it produces a force perpendicular to the yoke at the piston connection. From the sum of the moments about B, the magnitude of this force can be determined.

$$\Sigma M_B = 0 \tag{19}$$

$$F_{BAZ} - \frac{FAB}{2} (0.3) = 0$$

$$F_{BAZ} = FAB (0.15)$$

$$F_{BAZ} = 1{,}549 \text{ lb} (0.15)$$

$$F_{BAZ} = 232 \text{ lb}$$

Since FBA is known, the forces in the yoke connector (fig. 14) can now be determined. A torque (T) will be present on the connector from the two offset FBA forces.

8

$$T = 0.75 \text{ FBA} \qquad (20)$$

$$T = (0.75) (1,549 \text{ lb})$$

$$T = 1,162 \text{ in.-lb}$$

This torque will cause stress in the end posts. The maximum compression force (F) which the piston must produce can now be solved.

$$F = 2 \text{ FBA sin } 17° \qquad (21)$$

$$F = 2 (1,549 \text{ lb}) \sin 17°$$

$$F = 906 \text{ lb}$$

It must be remembered that this maximum compression force includes dynamic forces. When an analysis excluding the dynamic forces is performed, the initial force which the piston produces is 886 pounds.

A similar analysis can be completed for gripping a charge. The result is that the piston will have a working force of 225 pounds and a maximum force of 234 pounds.

KINEMATIC ANALYSIS

A kinematic analysis of the mechanism was conducted to determine if the dynamic forces of the moving links should be included. The gripper was modeled as an offset slider crank mechanism. The velocity of the piston was assumed constant since acceleration, once the mechanism is moving, is approximately zero. Position, velocity, and acceleration of different points on the mechanism were calculated as a function of piston velocity. The analysis, the program, and a sample program output are shown in appendix C.

The angular acceleration and the acceleration of the center of gravity of link R3 for a closing time of 1 second are shown in figure 15. The linear and angular accelerations for link R2 are of the same magnitude. Since the accelerations are small and the crank is almost balanced, the forces stemming from the movement of the links are not included.

STRESS ANALYSIS

This section provides details of the stress analysis of the various components of the gripper. The pins at points A, B, and C are detailed in figure

16. The pin at point A is in single shear at two places (fig. 17). Due to symmetry, the shear stresses (τ) are equal at both shear points. For circular cross sections, the maximum shear stress is at the center and can be calculated as:

$$\tau_{max} = \frac{16 \ FBA}{3 \ \pi \ d^2} \tag{22}$$

For the pin at point A,

$$\tau_{max} = \frac{16 \ (1,549 \ lb)}{3 \ \pi \ (0.3125 \ in.)^2} \tag{23}$$

$$\tau_{max} = 27,000 \ psi$$

The maximum shear stress theory, which is used throughout the design, states that the maximum yield strength (Sy) should be at least twice the maximum shear stress, or

$$Sy_{min} = 2 \ \tau_{max} \tag{24}$$

For the pin at point A,

$$Sy_{min} = 2 \ (27,000 \ psi) \tag{25}$$

$$Sy_{min} = 54,000 \ psi$$

The material used to make the pins has a yield strength of 120,000 psi. The factor of safety (FS) is the ratio of the yield strength to the minimum required yield strength.

$$FS = \frac{Sy}{Sy_{min}} \tag{26}$$

For the pin at point A,

$$FS = \frac{120,000 \ psi}{54,000 \ psi} \tag{27}$$

$$FS = 2.2$$

The pin at point B is in double shear with the same force as the pin at point A but has a smaller diameter (fig. 18). For a pin in double shear, the maximum shear stress will be half that of a pin in single shear.

$$\tau_{max} = \frac{8FAB}{3 \ \pi \ d^2} \tag{28}$$

10

For the pin point at B,

$$\tau_{max} = \frac{8\ (1{,}549\ lb)}{3\ \pi\ (0.25\ in.)^2} \tag{29}$$

$$\tau_{max} = 21{,}000\ psi$$

The minimum yield strength and factor of safety can be calculated using equations 24 and 26, respectively:

$$Sy_{min} = 2\ \tau_{max} \tag{24}$$

$$Sy_{min} = 2\ (21{,}000\ psi) \tag{30}$$

$$Sy_{min} = 42{,}000\ psi$$

$$FS = \frac{Sy}{Sy_{min}} \tag{26}$$

$$FS = \frac{120{,}000\ psi}{42{,}000\ psi} \tag{31}$$

$$FS = 2.9$$

The pin at point C (fig. 19) is also in double shear. The pin's maximum shear stress, minimum yield strength, and factor of safety can be calculated by equations 28, 24, and 26, respectively:

$$\tau_{max} = \frac{8Fc}{3\ \pi\ d^2} \tag{28}$$

$$\tau_{max} = \frac{8\ (2{,}489\ lb)}{3\ \pi\ (0.25\ in.)^2} \tag{32}$$

$$\tau_{max} = 33{,}800\ psi$$

$$Sy_{min} = 2\tau_{max} \tag{24}$$

$$Sy_{min} = 2\ (33{,}800\ psi) \tag{33}$$

11

$$Sy_{min} = 67,600 \text{ psi}$$

$$FS = \frac{Sy}{Sy_{min}} \qquad (26)$$

$$FS = \frac{120,000 \text{ psi}}{67,600 \text{ psi}} \qquad (34)$$

$$FS = 1.8$$

The next component discussed is the finger (fig. 20), since its dimensions are critical to the design of other pieces. The distance between B and C as well as the shape of the curved portion was determined by the working area and the conceptual analysis of the mechanism. The cross sectional area was determined by the strength requirements. The stress and strength calculations for three of the critical sections are presented here. Section B′-B′ has bearing stress imparted by the pin as well as a shear (tear out) stress. The bearing stress (σ) can be approximated by the following relationship:

$$\sigma = \frac{FAB}{t\,d} \qquad (35)$$

where

t = thickness of section (in.)

d = diameter of hole (in.)

For this section, t is 0.5 inch and d is 0.25 inch. There are two components to the bearing stress at this point, σ_x, and σ_y. They can be calculated using equation 35.

$$\sigma_x = \frac{-1,549 \text{ lb cos } 17°}{(0.5 \text{ in.}) (0.25 \text{ in.})} \qquad (36)$$

$$\sigma_x = -11,800 \text{ psi}$$

$$\sigma_y = \frac{-1,549 \text{ lb sin } 17°}{(0.5 \text{ in.}) (0.25 \text{ in.})} \qquad (37)$$

$$\sigma_y = -3,600 \text{ psi}$$

The minus notation refers to a compressive stress.

The shear stress acts only through the left-hand portion of the cross section. For a rectangular cross section, the maximum shear stress is at the center and can be calculated using the following relationship:

$$\tau = \frac{3}{2} \frac{FAB}{A} \qquad (38)$$

12

where

$$A = \text{cross sectional area (in.}^2).$$

Since the shear stress acts only through the left-hand section, A is 0.24 in.^{2}

$$\tau_{xy} = \frac{3}{2} \frac{(1,549 \text{ lb}) \cos 17°}{0.24 \text{ in.}^2} \tag{39}$$

$$\tau_{xy} = 9,260 \text{ psi}$$

With the use of Mohr's circle maximum shear stress can be calculated from the individual stresses using the following relationship:

$$\tau_{max} = \left(\left(\frac{\sigma_x - \sigma_y}{2} \right)^2 + \tau_{xy}^2 \right)^{1/2} \tag{40}$$

For this section,

$$\tau_{max} = \left(\left(\frac{-11,800 \text{ psi} - (-3,600 \text{ psi})}{2} \right)^2 + (9,260 \text{ psi})^2 \right)^{1/2} \tag{41}$$

$$\tau_{max} = 10,100 \text{ psi}$$

With the use of equation 24, the minimum yield strength can be determined.

$$Sy_{min} = 2 \tau_{max} \tag{24}$$

$$Sy_{min} = 2 (10,100 \text{ psi}) \tag{42}$$

$$Sy_{min} = 20,200 \text{ psi}$$

The finger has a minimum yield strength of 120,000 psi. The factor of safety for this cross section can now be solved using equation 26.

$$FS = \frac{Sy}{Sy_{min}} \tag{26}$$

$$FS = \frac{120,000 \text{ psi}}{20,200 \text{ psi}} \tag{43}$$

13

FS = 5.9

The most critical stresses are at section C′-C′. They include a bearing stress from the pin, a bending stress due to the moment, and a shear stress. The bearing stress is almost constant throughout the right-hand side. The bending moment increases from the center to a maximum tensile stress at the right outer edge. The shear stress is a parabolic function which is zero at the edge of the hole and at the outer edge of the section with maximum stress halfway between. The effect of the bending stress is greater than that of the shear stress. For this reason, the stresses at the right outer edge are analyzed.

As reported in reference 1, the maximum tensile stress will be twice what it would be were the hole not present. This is true for ratios of hole diameter to width less than 5. From this, it is evident that the tensile stress at the edge of the hole can be calculated from the following:

$$\sigma_y = \frac{6M}{t\,D^2} \tag{44}$$

where

M = Moment (in.-lb)

t = Thickness of section (in.)

D = Width of section (in.)

For the section to be studied,

M = 1,549 lb (cos 17°) x 2.387 in. = 3,686 in.-lb

t = 1.0 in.

D = 1.2 in.

$$\sigma_y = \frac{6\,(3{,}686 \text{ in.-lb})}{(1.0 \text{ in.})\,(1.2 \text{ in.})^2} \tag{45}$$

$$\sigma_y = 15{,}400 \text{ psi}$$

The compressive stress in the x direction can be calculated using equation 35 and a value of 2253 pounds for Cx.

$$\sigma_x = \frac{Cx}{t\,d} \tag{35}$$

14

$$\sigma_x = \frac{2,253 \text{ lb}}{(0.48 \text{ in.}) \ (0.25 \text{ in.})} \tag{46}$$

$$\sigma_x = -18,775 \text{ psi}$$

The shear stress in the x-y direction is zero at this point, so the maximum shear stress can be calculated using equation 40.

$$\tau_{max} = \left(\left(\frac{\sigma_x - \sigma_y}{2} \right)^2 + \tau_{xy}^2 \right)^{1/2} \tag{40}$$

$$\tau_{max} = \left(\left(\frac{18,775 \text{ psi} - 15,400 \text{ psi}}{2} \right)^2 \right)^{1/2} \tag{47}$$

$$\tau_{max} = 17,100 \text{ psi}$$

Equations 24 and 26 may now be used to calculate the minimum yield strength and the factor of safety at this section.

$$Sy_{min} = 2 \ \tau_{max} \tag{24}$$

$$Sy_{min} = 2 \ (17,100 \text{ psi}) \tag{48}$$

$$Sy = 34,200 \text{ psi}$$

$$FS = \frac{Sy}{Sy_{min}} \tag{26}$$

$$FS = \frac{120,000 \text{ psi}}{34,200 \text{ psi}} \tag{49}$$

$$FS = 3.5$$

The stress at section D´-D´ is caused by bending and shear. Again, the stress is greatest at the inner edge. The tension stress due to bending can be calculated using the following relationship:

$$\sigma = \frac{M \ c}{I} \tag{50}$$

where

c = distance between neutral axis and point of calculation (in.)

I = moment of inertia (in.^{4})

The moment of inertia for a rectangular cross section is

$$I = \frac{1}{12} b h^3 \tag{51}$$

where

h = height of section (in.)

b = base of section (in.)

For this section,

b = 2.0 in.

h = 0.7 in.

The moment of inertia can be calculated using equation 52.

$$I = \frac{1}{12} (2.0 \text{ in.}) (0.7 \text{ in.})^3 \tag{52}$$

$$I = 0.057 \text{ in.}^4$$

The distance between the point of calculation and the neutral axis is 0.35 inch. The moment on this section is 2,058 inch-pounds. The tensile stress can now be calculated by substituting into equation 50.

$$\sigma_y = \frac{M \; c}{I} \tag{50}$$

$$\sigma_y = \frac{(2,058 \text{ in.-lb}) (0.35 \text{ in.})}{(0.057 \text{ in.}^4)} \tag{53}$$

$$\sigma_y = 12,600 \text{ psi}$$

There are no other stresses on this section, so equation 40 can be used to solve for the maximum shear stress.

$$\tau_{max} = \left(\left(\frac{\sigma_x - \sigma_y}{2} \right)^2 + \tau_{xy} \right)^{1/2} \tag{40}$$

$$\tau_{max} = \left(\left(\frac{-12,600 \text{ psi}}{2} \right)^2 \right)^{1/2} \tag{54}$$

$$\tau_{max} = 6,300 \text{ psi}$$

The maximum yield strength and factor of safety can now be calculated.

$$Sy_{min} = 2 \tau_{max} \tag{24}$$

$$Sy_{min} = 2 (6,300 \text{ psi}) \tag{55}$$

$$Sy_{min} = 12,600 \text{ psi}$$

$$FS = \frac{Sy}{Sy_{min}} \tag{26}$$

$$FS = \frac{120,000 \text{ psi}}{12,600 \text{ psi}} \tag{56}$$

$$FS = 9.5$$

The finger connects to the yoke by the pin at B (fig. 21). There is bearing stress at pins B and A. There is also a bending stress at section A′-A′. These are critical sections and are analyzed separately.

For calculation of the bearing stress at section B′-B′, equation 35 can be used. The total contact area is used.

$$\sigma_x = \frac{FAB}{t \; d} \tag{35}$$

$$\sigma_x = \frac{-1,549 \text{ lb}}{(0.5 \text{ in.}) \; (0.25 \text{ in.})} \tag{57}$$

$$\sigma_x = -12,400 \text{ psi}$$

Again, equation 40 is used to calculate the maximum shear stress; however, since there is only one component, it reduces to the following:

$$\tau_{max} = \pm \frac{\sigma}{2} \tag{58}$$

$$\tau_{max} = \pm \frac{-12,400 \ psi}{2} \tag{59}$$

$$\tau_{max} = 6,200 \ psi$$

For this section, the maximum shear stress is 6,200 psi. Since the shear strength of the yoke is 120,000 psi, the factor of safety is 19.4.

At section A´-A´, t is 0.3 inch and d is 0.3125 inch. The bearing stress here is

$$\sigma_x = \frac{FAB}{t \ d} \tag{35}$$

$$\sigma_x = \frac{-1,549 \ lb}{(0.3 \ in.)(0.3125 \ in.)} \tag{60}$$

$$\sigma_x = -16,500 \ psi$$

There is an added bending moment at A´-A´ which can be calculated using equation 50. This has a rectangular cross section where

$$I = 0.001 \ in.^4$$

$$C = 0.5 \ in.$$

$$M = 51 \ in.-lb$$

$$\sigma_y = \frac{M \ c}{I} \tag{50}$$

$$\sigma_y = \frac{(51 \ in.-lb)(0.5 \ in.)}{(0.001 \ in.^4)} \tag{61}$$

$$\sigma_y = 25,500 \ psi$$

There is no shear stress in the x-y plane, so the maximum shear stress at this section can now be calculated using equation 40.

$$\tau_{max} = \left(\left(\frac{\sigma_x - \sigma_y}{2} \right)^2 + \tau_{xy}^2 \right)^{1/2} \tag{40}$$

$$\tau_{max} = \left(\left(\frac{-16,500 \ psi - 25,500 \ psi}{2} \right)^2 \right)^{1/2} \tag{62}$$

$$\tau_{max} = 21{,}000 \text{ psi}$$

Again, with the use of equations 24 and 26, Sy_{min} is 42,000 psi and the FS is 2.9.

The yokes attach to the piston via a connector (fig. 22). There is a bearing stress in the pin resulting from the torque it must transmit. The maximum bearing stress is at A'-A' and can be calculated by equation 35. Assuming half the connecting area withstands the bearing stress imparted by one yoke, t is 0.2 inch.

$$\sigma = \frac{FAB}{t \ d} \tag{35}$$

$$\sigma = \frac{-1{,}549 \ \text{lb}}{(0.5 \ \text{in.}) \ (0.25 \ \text{in.})} \tag{63}$$

$$\sigma = -24{,}800 \text{ psi}$$

Combining equations 58 and 24,

$$Sy_{min} = \sigma \tag{64}$$

$$Sy_{min} = 24{,}800 \text{ psi}$$

The factor of safety can be solved using equation 26 with Sy having a value of 120,000 psi.

$$FS = \frac{Sy}{Sy_{min}} \tag{26}$$

$$FS = \frac{120{,}000 \ \text{psi}}{24{,}800 \ \text{psi}} \tag{65}$$

$$FS = 4.8$$

The last item discussed is the saddle (fig. 23). Two critical sections are involved. First is the bearing and tearout area at C. Second is the combined bending and compression at section E'-E'.

The bearing stress at C can be calculataed by equation 35.

$$\sigma_x = \frac{FC}{t \ d} \tag{35}$$

$$\sigma_x = \frac{2{,}489 \text{ lb}}{(1.0 \text{ in.}) \ (0.25 \text{ in.})} \tag{66}$$

$$\sigma_x = 10{,}000 \text{ psi}$$

The tearout stress is in the y direction and is caused by the shear. Since this is a rectangular cross section, the maximum shear in the x-y direction can be calculated using equation 38. The area is 0.4 in.^{2}.

$$\tau_{xy} = \frac{3}{2} \frac{FC}{A} \tag{38}$$

$$\tau_{xy} = \frac{3}{2} \frac{2{,}489 \text{ lb}}{0.4 \text{ in.}^2} \tag{67}$$

$$\tau_{xy} = 9{,}300 \text{ psi}$$

The maximum shear at this section can be calculated using equation 40.

$$\tau_{max} = \left(\left(\frac{\sigma_x - \sigma_y}{2} \right)^2 + \tau_{xy}^2 \right)^{1/2} \tag{40}$$

$$\tau_{max} = \left(\left(\frac{10{,}000 \text{ psi}}{2} \right)^2 + (9{,}300 \text{ psi})^2 \right)^{1/2} \tag{68}$$

$$\tau_{max} = 10{,}500 \text{ psi}$$

The minimum yield strength must be 21,200 psi. This results in a factor of safety of 5.6 since the material has a yield strength of 120,000 psi.

Section E´-E´ (fig. 23) is a curved beam in bending. Equations 69 through 72 are taken from reference 2. The meaning of the symbols is shown in figure 24.

$$rn = \frac{\Sigma \, A}{\Sigma \left(b \, \ln \left(\frac{r_o}{r_i} \right) \right)} \tag{69}$$

$$rn = \frac{(1.2 \text{ in.}^2)}{2 \, \ln \left(\frac{3.725 \text{ in.}}{3.125 \text{ in.}} \right)} \tag{70}$$

$$rn = 3.416 \text{ inches}$$

$$e = r_g - rn \tag{71}$$

$$e = 3.425 \text{ in.} - 3.416 \text{ in.} \tag{72}$$

$$e = 0.009 \text{ inch}$$

The bending stress at the inner surface, which is the location of maximum stress, can now be calculated.

$$\sigma_i = \frac{M \; ci}{A \; e \; ri} \tag{73}$$

$$\sigma_i = \frac{\left[(2,489 \text{ lb}) \; (1.1 \text{ in.})\right] \; (0.3 \text{ in.})}{(1.2 \text{ in.}^2) \; (0.009 \text{ in.}) \; (3.125 \text{ in.})} \tag{74}$$

$$\sigma = 25,000 \text{ psi}$$

With equations 24 and 26, Sy_{min} is 50,000 psi and the factor of safety is 2.4.

PISTON RATIONALIZATION

The piston must travel 1.6 inches between the mechanism's fully opened and fully closed positions. Since a piston should work only over 80% of its stroke, the stroke should be 2 inches. As shown in the Force Analysis section, the piston must produce forces of 906 pounds and 234 pounds.

The piston selected for this use is double acting and has a 1.63-inch bore with a 2-inch stroke (fig. 25).

The piston has a maximum pressure rating of 500 psi. Its operating pressures can be calculated as shown. Pressure (P) is the force divided by area.

$$P = \frac{F}{A} \tag{75}$$

The area of the piston is

$$A = \frac{\pi \; d^2}{4} \tag{76}$$

where

d = diameter of piston (1.625 in.)

$$A = \frac{\pi \ (1.625 \ \text{in.})^2}{4} \qquad\qquad (77)$$

$$A = 2.07 \ \text{in.}^2$$

When gripping a projectile, the piston must have a working force of 886 pounds. The piston's pressure at this force will be

$$Pwp = \frac{886 \ \text{lb}}{2.07 \ \text{in.}^2} \qquad\qquad (78)$$

$$Pwp = 427 \ \text{psi}$$

To properly grip a charge, the piston must produce a working force of 225 pounds. The piston's pressure at this force will be

$$Pwc = \frac{225 \ \text{lb}}{2.07 \ \text{in.}^2} \qquad\qquad (79)$$

$$Pwc = 109 \ \text{psi}$$

Due to dynamic forcing, the maximum force could be as much as 906 pounds. The pressure at this force level is

$$P_{max} = \frac{906 \ \text{lb}}{2.07 \ \text{in.}^2} \qquad\qquad (80)$$

$$P_{max} = 438 \ \text{psi}$$

Note that P_{max} is less than the 500 psi rating of the piston.

CONCLUSIONS AND RECOMMENDATIONS

The gripper introduced meets all the specifications detailed in this report. The gripper was designed to the dimensions of the largest object to be grasped; namely, the largest proposed dimension of the experimental uni charge.* After the dimensions of the uni charge are known, the gripper should be retooled to the dimensions of the largest object it must then grasp. This will not only result in a better grasp of a load, but will also reduce the stresses within the gripper.

Drawings of the gripper as presently configured are shown in appendix D. An artist's conception of the gripper precisely tooled to the contour of a projectile is shown in figure 26.

---

* The uni charge is a rigid-case propelling charge presently under development.

REFERENCES

1. R. B. Heywood, <u>Designing by Photoelasticity</u>, Adland and Son, Ltd., Great Britain, 1952.

2. Omer W. Blodgett, <u>Design of Weldments</u>, The James F. Lincoln Arc Welding Foundation, Cleveland, Ohio, 1963.

BIBLIOGRAPHY

1. Ferdinand P. Beer and E. Russell Johnston, Jr., <u>Mechanics of Materials</u>, McGraw-Hill Book Co., New York, 1981.

2. <u>Dimensioning and Tolerancing: ANSI Y14.5M</u>, American Society of Mechanical Engineers, New York, 1983.

3. J. Kammerer, <u>155MM Artillery Weapon Systems Reference Data Book</u>, U.S. Army Armament Research and Development Command, Dover, NJ, 1980.

4. Erik Oberg and F. D. Jones, <u>Machinery's Handbook: For Machine Shop and Drafting Room</u>, fourteenth edition, The Industrial Press, New York, 1949.

5. Raymond J. Roark and Warren C. Young, <u>Formulas for Stress and Strain</u>, fifth edition, McGraw-Hill Book Co., New York, 1975.

6. <u>Ryerson Stocks and Services Catalogue</u>, Joseph T. Ryerson and Son, Inc., Jersey City, NJ, 1980.

7. Joseph Edward Shigley and John Joseph Uicker, Jr., <u>Theory of Machines and Mechanisms</u>, McGraw-Hill Book Co., New York, 1980.

Figure 1. Integrated Smart Artillery Synthesis (ISAS) robotic demonstrator

Figure 2. Motion without tilt

Figure 3. Motion with tilt

Figure 4. Robot in flexed position

Figure 5. Three-piston gripper concept

Figure 6.   Inflatable gasket gripper concept

Figure 7.   Long-stroke concept

Figure 8.   Short-stroke concept

Figure 9.   Generalized gripper schematic

31

Figure 10.   Worst case condition for gripping

Figure 11.   Force analysis layout

Figure 12. Forces acting upon finger

Figure 13. Forces acting upon yoke

Figure 14. Forces acting upon yoke connector

Figure 15. Angular acceleration and acceleration of center of gravity of link 3 versus piston displacement

Figure 16. Pin locations

Figure 17. Stress locations on
pin at point A

Figure 18. Stress locations on
pin at point B

Figure 19.   Stress locations on pin at point C

Figure 20.   Stress locations on finger

Figure 21. Stress locations on yoke

Figure 22. Stress location on yoke connector

Figure 23. Stress locations on saddle

where:

A = area of cross-section

e = shift of neutral axis from C.G. = $r_g - r_n$

r_n = radius neutral axis from center of curvature

c_o = distance outer fiber to neutral axis = $r_o - r_n$

c_i = distance inner fiber to neutral axis = $r_n - r_i$

r_g = radius center of gravity from center of curvature

d = distance line of force to neutral axis of section

Excerpt from <u>Design of Weldments</u> by Omer W. Blodgett, printed by The James F. Lincoln Arc Welding Foundation, Cleveland, Ohio, 1963.

Figure 24.   Curved beam analysis

39

Figure 25. "Pancake" hydraulic cylinder

Figure 26. ISAS robotic gripper

APPENDIX A

PRODUCT SEARCH

Manufacturer	Gripper evaluation	Applicability	Remarks
O. S. Walker Co., Inc.	Magnetic force only;	No	
PHD, Inc.	Not enough force; gripper too small.	No	Not interested
Mack Corporation			
VSI Automation	Assembly gripper.	No	
Compact Air Products	Working diameter is less than 6 in., maximum opening is 5 in.; possible to redesign.	Possible	
Simirt	Not enough force (10 lb max).	No	
R&I Mfg. Company, Inc.	Working diameter is less than 6 in. Complete redesign is necessary.	No	
Barrington Automation, Ltd.	Not enough force; gripper too small.	No	
Kennametal, Inc.	Not enough force; gripper too small.	No	Primarily metal cutting.
Robohand, Inc.	Not enough force; gripper too small.	No	Willing to design gripper.
Air Technical Industries	Has numerous grippers.	Possible	Needs guidance to choose the best adaptable gripper. Sensors are not included. Customer's design not available. Modification probably unavailable. Grippers designed to handle raw material. Grippers usually sold with robots.
Design Technolgy Corporation	No	No	Consulting company for automation system.
Positech Corporation	No	No	Interested only in selling robotic system.
Coleman Equipment, Inc.	Provides variety of grippers.	Perhaps	Needs more specific information.

43

APPENDIX B

SPATIAL ANALYSIS

(DERIVATION OF EQUATIONS, FORTRAN PROGRAM, AND PROGRAM OUTPUT)

Derivation of Equations

A FORTRAN program was developed to study trends in the mechanism when its characteristics were varied (fig. B-1). Following is the list of variables:

D   Distance between center line of mechanism and low end of piston stroke (in.)

R   Distance between center line of mechanism and lower left hand pin (in.)

T2 Θ_2 (rad)

T1 Θ_1 (rad)

R_2 Length of link R2 (in.)

R_3 Length of link R3 (in.)

y   Longitudinal distance between center line of projectile and lower left-hand pin (in.)

x   Distance gripper displaces (in.)

S   Distance between center pivot and low end of piston stroke (in.)

With the law of cosines, lengths L and h can be determined as a function of R_2, R_3, and Θ.

$$L^2 = R_2^2 + R_3^2 - 2 R_2 R_3 \cos \Theta_2 \tag{B-1}$$

$$h^2 = R_2^2 + R_3^2 - 2 R_2 R_3 \cos \Theta_1 \tag{B-2}$$

Subtracting equation B-2 from B-1 yields

$$L^2 - h^2 = - 2 R_2 R_3 \cos \Theta_2 + 2 R_2 R_3 \cos \Theta_1 \tag{B-3}$$

This equation can be solved for R_2

$$R_2 = \frac{L^2 - h^2}{2 (\cos \Theta_1 - \cos \Theta_2) R_3} \tag{B-4}$$

47

Substituting equation B-4 into B-2 yields

$$L^2 = \left(\frac{L^2 - h^2}{2 (\cos \Theta_1 - \cos \Theta_2)} \right)^2 \frac{1}{R_3^2} + R_3^2 - \frac{2 R_3 (L^2 - h^2) \cos \Theta_2}{2 R_3 (\cos \Theta_1 - \cos \Theta_2)} \quad (B-5)$$

Multiplying equation B-5 by R_3 and setting it to zero yields

$$R_3^4 - R_3^2 \left(\frac{(L^2 - h^2) \cos \Theta_2}{(\cos \Theta_1 - \cos \Theta_2)} + L^2 \right) + \left(\frac{(L^2 - h^2)}{2 (\cos \Theta_1 - \cos \Theta_2)} \right)^2 = 0 \quad (B-6)$$

Since R and D form a right angle, pathagarien theorem can be used to determine L and h as a function of R, D, and S

$$L^2 = R^2 + D^2 \tag{B-7}$$

$$h^2 = R^2 + (D + S)^2 \tag{B-8}$$

When equations B-7 and B-8 are substituted into equation B-6 the result is an equation relating R_3 to known parameters

$$R_3^4 - R_3^2 \left(\frac{\left((R^2 + D^2) - \left(R^2 + (D + S)^2\right)\right)\cos \Theta_2}{(\cos \Theta_1 - \cos \Theta_2)} + R^2 + D^2 \right) +$$

$$\left(\frac{(R^2 + D^2) - \left(R^2 + (D + S)^2\right)}{2 (\cos \Theta_1 - \cos \Theta_2)} \right)^2 = 0 \quad (B-9)$$

$$R_3^4 - R_3^2 \left(\frac{\left(D^2 - (D + S)^2\right) \cos \Theta_2}{(\cos \Theta_1 - \cos \Theta_2)} + R^2 + D^2 \right) +$$

$$\left(\frac{D^2 - (D + S)^2}{2 (\cos \Theta_1 - \cos \Theta_2)} \right) = 0 \quad (B-10)$$

48

There are four roots to this equation, two pairs of which are equal. Of the two remaining, one is positive. To find this root the following steps may be used.

Let A and B equal the following:

$$A = - \frac{\left(D^2 - (D + S)^2\right) \cos \Theta_2}{(\cos \Theta_1 - \cos \Theta_2)} + R^2 + D^2 \tag{B-11}$$

$$B = \frac{D^2 - (D + S)^2}{2 (\cos \Theta_1 - \cos \Theta_2)} \tag{B-12}$$

R_3 can now be found.

$$R_3 = + \left(- \frac{A}{2} \pm \frac{(-A^2 - 4B)^{1/2}}{2} \right)^{1/2} \tag{B-13}$$

Since R_3 is known, R_2 can be determined by equation B-4.

$$R_2 = \frac{L^2 - h^2}{2 (\cos \Theta_1 - \cos \Theta_2) R_3} \tag{B-4}$$

$$R_2 = \frac{D^2 - (D + S)^2}{2 (\cos \Theta_1 - \cos \Theta_2) R_3} \tag{B-14}$$

Calculations are now made to see if the mechanism stays in its intended envelope. If it stays within the envelope, the link lengths of the mechanism are printed out.

Figure B-1.   FORTRAN developed gripper concept

FORTRAN Program

```
PROGRAM MECH 1 (OUTPUT,TAPE6=OUTPUT)
IMPLICIT REAL (A-Z)
COMMON C1
T2=95.*3.1415927/180.
WRITE (6,100)
100     FORMAT (1H1,12X,"R",9X,"D",9X,"S",8X,"T1",7X,"R3",8X,"R2",9X,"X")
Y=1
C1=0
DO50 T1=121,135
T1A=T1*3.1415927/180.
DO 40 S=-.3,1.5,.1
DO 30 R=3.3,4.5,.1
DO 20 D=-4.,5.3,.1
IF(D+S.GT.5.5) GOTO 20
CT=COS(T1A)-COS(T2)
DS=D*D-(D+S)*(D+S)
E=DS*COS(T2)/CT+R*R+D*D
F=(DS/(2*CT))**2
IF(E*E.LT.4.*F) GOTO 20
G=(E*E-4.*F)**.5
IF (E.LT.G) GOTO 20
R3=((E-G)/2)**.5
CALLHELP (D,R,S,T1A,T2,DS,R3,Y,R2,T1,CT)
R3=R2
CALLHELP (D,R,S,T1A,T2,DS,R3,Y,R2,T1,CT)
20      CONTINUE
30      CONTINUE
40      CONTINUE
50      CONTINUE
STOP
END
SUBROUTINE HELP (D,R,S,T1A,T2,DS,R3,Y,R2,T1,CT)
COMMON C1
R2=DS/2/CT/R3
A=ASIN(R2*SIN(T2)/(R*R+D*D)**.5)
```

```
      B=ASIN(R2*SIN(T1A)/(R*R+(D+S)*(D+S))**.5)
      C=ATAN((D+S)/R)
      H=ATAN(D/R)
      PH=A-B-C+H
      X=Y*SIN(PH)
      IF((X.GT..25).AND.(R2*COS(3.142-A-T2).LT.4.25)) THEN
      WRITE (6,110) R,D,S,T1,R3,R2,X
110   FORMAT(5X,4F10.2,3F10.4)
      C1=C1+1
      ENDIF
      IF(C1.EQ.50) THEN
      WRITE (6,100)
100   FORMAT (1H1,12X,"R",9X,"D",9X,"S",8X,"T1",7X,"R3",8X,"R2",9X,"X")
      C1=0
      ENDIF
      RETURN
      END
```

52

Program Output

R	D	S	T1	R3	R2	X
3.30	4.00	.90	121.00	2.0373	4.5943	.2519
3.30	4.00	1.00	123.00	2.1756	4.5213	.2576
3.30	4.10	1.00	123.00	2.1853	4.6013	.2622
3.40	4.00	1.00	123.00	2.1311	4.6156	.2620
3.30	4.00	1.00	124.00	2.0865	4.5689	.2765
3.30	4.20	1.10	124.00	2.4344	4.5469	.2522
3.30	4.30	1.10	124.00	2.4399	4.6321	.2575
3.30	4.40	1.10	124.00	2.4448	4.7183	.2627
3.40	4.10	1.10	124.00	2.3731	4.5661	.2524
3.40	4.20	1.10	124.00	2.3818	4.6473	.2575
3.50	4.00	1.10	124.00	2.3102	4.5896	.2530
3.50	4.10	1.10	124.00	2.3219	4.6669	.2577
3.30	4.00	1.10	125.00	2.3165	4.4419	.2615
3.30	4.10	1.10	125.00	2.3246	4.5236	.2668
3.30	4.20	1.10	125.00	2.3319	4.6065	.2721
3.40	4.30	1.10	125.00	2.3383	4.6905	.2772
3.40	4.00	1.10	125.00	2.2651	4.5427	.2671
3.50	4.10	1.10	125.00	2.2753	4.6217	.2720
3.50	4.00	1.10	125.00	2.2169	4.6413	.2722
3.60	4.30	1.20	125.00	2.5780	4.6890	.2525
3.30	4.20	1.20	126.00	2.5117	4.7146	.2534
3.30	4.00	1.10	126.00	2.2244	4.4944	.2869
3.30	4.10	1.10	126.00	2.2332	4.5751	.2861
3.40	4.20	1.10	126.00	2.2411	4.6571	.2911
3.30	4.00	1.10	126.00	2.1777	4.5907	.2860
3.30	4.20	1.20	126.00	2.5819	4.4563	.2548
3.40	4.30	1.20	126.00	2.5844	4.5446	.2609
3.40	4.10	1.20	126.00	2.5136	4.4820	.2556
3.40	4.20	1.20	126.00	2.5201	4.5655	.2614
3.50	4.30	1.20	126.00	2.5258	4.6500	.2671
3.50	4.00	1.20	126.00	2.4439	4.5117	.2568
3.50	4.10	1.20	126.00	2.4541	4.5906	.2622
3.50	4.20	1.20	126.00	2.4633	4.6708	.2675
3.60	4.00	1.20	126.00	2.3868	4.6197	.2633

53

.2682	4.6958	2.3991	126.00	1.20	4.10	3.60
.2997	4.5393	2.1424	127.00	1.10	4.00	3.30
.3047	4.6194	2.1515	127.00	1.10	4.10	3.30
.3044	4.6322	2.0994	127.00	1.10	4.00	3.40
.2632	4.3531	2.4639	127.00	1.20	4.00	3.30
.2693	4.4374	2.4696	127.00	1.20	4.10	3.30
.2754	4.5228	2.4745	127.00	1.20	4.20	3.30
.2813	4.6091	2.4788	127.00	1.20	4.30	3.30
.2702	4.4625	2.4035	127.00	1.20	4.00	3.40
.2758	4.5433	2.4120	127.00	1.20	4.10	3.40
.2813	4.6254	2.4196	127.00	1.20	4.20	3.40
.2868	4.7086	2.4264	127.00	1.20	4.30	3.40
.2766	4.5681	2.3479	127.00	1.20	4.00	3.50
.2818	4.6461	2.3587	127.00	1.20	4.10	3.50
.2825	4.6710	2.2962	127.00	1.20	4.00	3.60
.2515	4.5537	2.6348	127.00	1.20	4.10	3.60
.2573	4.6342	2.6435	127.00	1.30	4.20	3.60
.2537	4.5941	2.5567	127.00	1.30	4.00	3.70
.2590	4.6698	2.5693	127.00	1.30	4.10	3.70
.2643	4.7470	2.5807	127.00	1.30	4.20	3.70
.2609	4.7085	2.4946	127.00	1.30	4.00	3.80
.3179	4.5783	2.0685	127.00	1.10	4.00	3.30
.2833	4.4119	2.3673	128.00	1.20	4.10	3.30
.2892	4.4948	2.3742	128.00	1.20	4.20	3.30
.2950	4.5787	2.3803	128.00	1.20	4.00	3.30
.3007	4.6636	2.3856	128.00	1.20	4.10	3.30
.2897	4.5154	2.3131	128.00	1.20	4.20	3.40
.2951	4.5953	2.3223	128.00	1.20	4.30	3.40
.3005	4.6764	2.3306	128.00	1.20	4.00	3.40
.2956	4.6163	2.2625	128.00	1.20	4.10	3.50
.2544	4.3513	2.7417	128.00	1.30	4.20	3.30
.2563	4.3860	2.6639	128.00	1.30	4.00	3.40
.2630	4.4729	2.6671	128.00	1.30	4.10	3.40
.2585	4.4240	2.5854	128.00	1.30	4.20	3.50
.2646	4.5053	2.5934	128.00	1.30	4.10	3.50

.2707	4.5879	2.6003	128.00	1.30	4.20	3.50
.2665	4.5412	2.5187	128.00	1.30	4.00	3.60
.2720	4.6190	2.5296	128.00	1.30	4.10	3.60
.2776	4.6981	2.5393	128.00	1.30	4.20	3.60
.2737	4.6535	2.4579	128.00	1.30	4.00	3.70
.2788	4.7284	2.4710	128.00	1.30	4.10	3.70
.2523	4.6895	2.6549	128.00	1.40	4.00	3.90
.2574	4.7616	2.6703	128.00	1.40	4.10	3.90
.3026	4.4619	2.2819	129.00	1.20	4.00	3.30
.3083	4.5437	2.2895	129.00	1.20	4.10	3.30
.3139	4.6266	2.2963	129.00	1.20	4.20	3.30
.3085	4.5609	2.2323	129.00	1.20	4.00	3.40
.3137	4.6401	2.2419	129.00	1.20	4.10	3.40
.3139	4.6581	2.1857	129.00	1.20	4.20	3.50
.2619	4.2503	2.6233	129.00	1.30	4.00	3.30
.2691	4.3386	2.6252	129.00	1.30	4.10	3.30
.2762	4.4277	2.6265	129.00	1.30	4.20	3.30
.2709	4.3717	2.5504	129.00	1.30	4.00	3.40
.2774	4.4553	2.5564	129.00	1.30	4.10	3.40
.2838	4.5400	2.5615	129.00	1.30	4.20	3.40
.2789	4.4868	2.4850	129.00	1.30	4.00	3.50
.2848	4.5667	2.4941	129.00	1.30	4.10	3.50
.2906	4.6478	2.5021	129.00	1.30	4.20	3.50
.2862	4.5972	2.4253	129.00	1.30	4.00	3.60
.2916	4.6741	2.4367	129.00	1.30	4.10	3.60
.2928	4.7041	2.3702	129.00	1.30	4.20	3.70
.2522	4.4590	2.7797	129.00	1.30	4.00	3.60
.2555	4.5087	2.6918	129.00	1.30	4.10	3.70
.2616	4.5865	2.7024	129.00	1.40	4.00	3.70
.2644	4.6326	2.6198	129.00	1.40	4.10	3.80
.2698	4.7069	2.6333	129.00	1.40	4.00	3.80
.2723	4.7505	2.5548	129.00	1.40	4.10	3.90
.3211	4.5050	2.2052	130.00	1.20	4.00	3.30
.3267	4.5860	2.2134	130.00	1.20	4.10	3.30
.3321	4.6681	2.2207	130.00	1.20	4.20	3.30

.3266	4.6006	2.1594	130.00	1.20	4.00	3.40
.2831	4.3180	2.5195	130.00	1.30	4.00	3.30
.2899	4.4039	2.5235	130.00	1.30	4.10	3.30
.2966	4.4908	2.5268	130.00	1.30	4.20	3.30
.2911	4.4312	2.4552	130.00	1.30	4.00	3.40
.2974	4.5132	2.4624	130.00	1.30	4.10	3.40
.3035	4.5964	2.4687	130.00	1.30	4.20	3.40
.2984	4.5399	2.3964	130.00	1.30	4.00	3.50
.3041	4.6188	2.4061	130.00	1.30	4.10	3.50
.3098	4.6990	2.4149	130.00	1.30	4.20	3.50
.3051	4.6452	2.3421	130.00	1.40	4.00	3.60
.2534	4.2713	2.8315	130.00	1.40	4.10	3.40
.2571	4.3217	2.7402	130.00	1.40	4.00	3.50
.2643	4.4068	2.7445	130.00	1.40	4.10	3.50
.2673	4.4520	2.6600	130.00	1.40	4.10	3.60
.2737	4.5322	2.6685	130.00	1.40	4.00	3.60
.2762	4.5742	2.5890	130.00	1.40	4.10	3.70
.2820	4.6507	2.6005	130.00	1.40	4.00	3.70
.2843	4.6906	2.5247	130.00	1.40	4.10	3.80
.2895	4.7642	2.5386	130.00	1.40	4.00	3.80
.3392	4.5428	2.1359	130.00	1.20	4.10	3.30
.3446	4.6232	2.1444	131.00	1.20	4.00	3.30
.3031	4.3747	2.4289	131.00	1.30	4.10	3.30
.3097	4.4590	2.4342	131.00	1.30	4.00	3.30
.3161	4.5442	2.4388	131.00	1.30	4.10	3.30
.3105	4.4818	2.3708	131.00	1.30	4.20	3.40
.3165	4.5628	2.3789	131.00	1.30	4.00	3.40
.3224	4.6449	2.3860	131.00	1.30	4.10	3.40
.3172	4.5857	2.3171	131.00	1.30	4.20	3.50
.3228	4.6639	2.3273	131.00	1.30	4.00	3.50
.2562	4.1242	2.8045	131.00	1.40	4.10	3.30
.2650	4.2195	2.7994	131.00	1.40	4.00	3.30
.2684	4.2649	2.7119	131.00	1.40	4.10	3.40
.2760	4.3528	2.7137	131.00	1.40	4.00	3.40
.2787	4.3936	2.6325	131.00	1.40	4.10	3.50

.2855	4.4764	2.6388	131.00	1.40	4.10	3.50
.2878	4.5144	2.5620	131.00	1.40	4.00	3.60
.2939	4.5932	2.5717	131.00	1.40	4.10	3.60
.2959	4.6295	2.4984	131.00	1.40	4.00	3.70
.3015	4.7052	2.5105	131.00	1.40	4.10	3.70
.3567	4.5761	2.0727	132.00	1.20	4.00	3.30
.3223	4.4232	2.3483	132.00	1.30	4.00	3.30
.3286	4.5063	2.3546	132.00	1.30	4.10	3.30
.3348	4.5904	2.3601	132.00	1.30	4.20	3.40
.3291	4.5257	2.2951	132.00	1.30	4.00	3.40
.3349	4.6058	2.3037	132.00	1.30	4.10	3.40
.3407	4.6871	2.3114	132.00	1.30	4.20	3.40
.3354	4.6257	2.2455	132.00	1.30	4.00	3.50
.2793	4.2065	2.6878	132.00	1.40	4.00	3.30
.2874	4.2974	2.6870	132.00	1.40	4.00	3.30
.2898	4.3340	2.6087	132.00	1.40	4.10	3.40
.2970	4.4193	2.6128	132.00	1.40	4.00	3.40
.2990	4.4535	2.5387	132.00	1.40	4.00	3.50
.3055	4.5347	2.5464	132.00	1.40	4.00	3.50
.3073	4.5674	2.4754	132.00	1.40	4.10	3.60
.3132	4.6452	2.4857	132.00	1.40	4.00	3.60
.3148	4.6771	2.4174	132.00	1.40	4.00	3.70
.3738	4.6057	2.0148	132.00	1.40	4.00	3.30
.3407	4.4653	2.2758	133.00	1.40	4.10	3.30
.3469	4.5475	2.2828	133.00	1.20	4.20	3.30
.3529	4.6307	2.2890	133.00	1.30	4.00	3.30
.3471	4.5641	2.2266	133.00	1.30	4.10	3.40
.3528	4.6436	2.2355	133.00	1.30	4.00	3.40
.3006	4.2733	2.5886	133.00	1.30	4.10	3.30
.3082	4.3613	2.5903	133.00	1.40	4.00	3.30
.3100	4.3918	2.5187	133.00	1.40	4.10	3.40
.3169	4.4753	2.5243	133.00	1.40	4.00	3.40
.3184	4.5046	2.4556	133.00	1.40	4.10	3.50
.3247	4.5846	2.4641	133.00	1.40	4.10	3.50
.3260	4.6133	2.3978	133.00	1.40	4.00	3.60

.3318	4.6904	2.4086	133.00	1.40	4.10	3.60
.3586	4.5023	2.2101	134.00	1.30	4.00	3.30
.3646	4.5838	2.2175	134.00	1.30	4.10	3.30
.3704	4.6663	2.2242	134.00	1.30	4.20	3.30
.3646	4.5981	2.1641	134.00	1.30	4.00	3.40
.3206	4.3293	2.5018	134.00	1.40	4.00	3.30
.3280	4.4154	2.5053	134.00	1.40	4.10	3.30
.3292	4.4412	2.4388	134.00	1.40	4.00	3.40
.3359	4.5235	2.4454	134.00	1.40	4.10	3.40
.3370	4.5489	2.3811	134.00	1.40	4.00	3.50
.3431	4.6281	2.3901	134.00	1.40	4.00	3.50
.3442	4.6534	2.3276	134.00	1.40	4.00	3.60
.3759	4.5352	2.1500	135.00	1.30	4.10	3.30
.3818	4.6160	2.1578	135.00	1.30	4.00	3.30
.3817	4.6284	2.1067	135.00	1.30	4.00	3.40
.3398	4.3773	2.4247	135.00	1.40	4.10	3.30
.3468	4.4619	2.4293	135.00	1.40	4.00	3.30
.3477	4.4841	2.3670	135.00	1.40	4.10	3.40
.3541	4.5655	2.3743	135.00	1.40	4.00	3.40
.3550	4.5878	2.3135	135.00	1.40	4.10	3.50
.3609	4.6663	2.3229	135.00	1.40		3.50

APPENDIX C

KINEMATIC ANALYSIS

(DERIVATION OF EQUATIONS, FORTRAN PROGRAM, AND SAMPLE PROGRAM OUTPUT)

Derivation of Equations

The mechanism modeled is shown in figure C-1. Kinematic quantities are determined as a function of piston velocity and displacement. Piston velocity is assumed to be constant. Following is the list of variables used for the analysis.

VA   Velocity of point A (in./sec)

delta   Position of point A from closed position (in.)

W2K   Angular velocity of link R1 in z dirction (rad/sec)

W3K   Angular velocity of link R3 in z direction (rad/sec)

Alf2K   Angular acceleration of link R2 in z direction (rad/sec^2)

Alf3K   Angular acceleration of link R3 in z direction (rad/sec^2)

T2   Angle theta 2 (deg)

T3   Angle theta 3 (deg)

F   A point on R3

XI   Position of calculated point (x-dir) (in.)

XJ   Position of calculated point (y-dir) (in.)

VI   Velocity of calculated point (x-dir) (in./sec)

VJ   Velocity of calculated point (y-dir) (in./sec)

MAGV   Velocity of calculated point (magnitude) (in./sec)

AI   Acceleration of calculated point (x-dir) (in./sec^2)

AJ   Acceleration of calculated point (y-dir) (in./sec^2)

MAGA   Acceleration of calculated point (magnitude) (in./sec^2)

R   Distance to calculated point from point C (in.)

T   Angle of R from horizontal (rad)

Two approaches can be used to solve θ_2 and θ_3. The law of cosines may be used to relate the geometry in such a way as to produce complex equations which can be solved for θ_2 and θ_3. Since the computer is used for this analysis, a simplier method involving iteration is used. A loop equation can be written to state that the vector sum of all the link lengths is zero. Starting and ending

61

at the origin and letting $\hat{i}$ and $\hat{j}$ be unit vectors in the x and y directions, respectively,

$$- 3.3 \text{ in. } \hat{i} + R_3 (\cos \Theta_3 \, \hat{i} + \sin \Theta_3 \, \hat{j}) +$$

$$R_2 (\cos \Theta_2 \, \hat{i} + \sin \Theta_2 \, \hat{j}) - ds \, \hat{j} - 4 \text{ in. } \hat{j} = \overline{0}) \tag{C-1}$$

Separating the equation into its $\hat{i}$ and $\hat{j}$ components, two scaler equations can be written:

$$- 3.7 \text{ in. } + R_3 \cos \Theta_3 + R_2 \cos \Theta_2 = 0 \tag{C-2}$$

$$R_3 \sin \Theta_3 + R_2 \sin \Theta_2 = 0 \tag{C-3}$$

These equations can now be solved for Θ_2 and Θ_3:

$$\Theta_2 = \sin^{-1} \left((2.9 \text{ in. } + ds - R_3 \sin \Theta_3) / R_2 \right) \tag{C-4}$$

$$\Theta_3 = \cos^{-1} \left((3.7 \text{ in. } - R_2 \cos \Theta_2) / R_3 \right) \tag{C-5}$$

The angular velocities of links R_2 and R_3 can now be determined. The velocity of point A is known, so the velocity of point B can be determined as the velocity of A plus the velocity of point B with respect to point A.

$$\overline{V}_B = \overline{V}_A + \overline{V}_{B/A} \tag{C-6}$$

The velocity of point B with respect to point A is the cross product of the angular velocity of link R_2 (ω_2) with the displacement between points A and B. Assuming ω_2 is directed in the positive z direction ($\hat{k}$ unit vector), the following can be written:

$$\overline{V}_{B/A} = \omega_2 \, \hat{k} \times R_2 (-\cos \Theta_2 \, \hat{i} - \sin \Theta_2 \, \hat{j}) \tag{C-7}$$

Solving the cross product, equation C-6 can be rewritten:

$$\overline{V}_B = V_A \, \hat{j} - \omega_2 R_2 \cos \Theta_2 \, \hat{j} + \omega_2 R_2 \sin \Theta_2 \, \hat{i} \tag{C-8}$$

62

In the same manner, it can be written:

$$\overline{V}_B = \overline{V}_C + V_{B/C} \qquad (C-9)$$

The velocity of point C is zero,

$$\overline{V}_C = \overline{0} \qquad (C-10)$$

The velocity of point B with respect to point C is the cross product of the angular velocity of link R_3 (ω_3) with the displacement between points C and B. As with ω_2, ω_3 is assumed to be the z direction.

$$\overline{V}_{B/C} = \omega_3 \, \hat{k} \times R_3 \, (\cos \, \Theta_3 \, \hat{i} + \sin \, \Theta_3 \, \hat{j}) \qquad (C-11)$$

Solving the cross product and substituting into equation C-9,

$$\overline{V}_B = \omega_3 \, \hat{k} \times R_3 \, (\cos \, \Theta_3 \, \hat{i} + \sin \, \Theta_3 \, \hat{j}) \qquad (C-12)$$

Equations C-8 and C-12 can be solved and two scaler equations can be written for the x and y directions.

$$V_A - \omega_2 \, R_2 \, \cos \, \Theta_2 = \omega_3 \, R_3 \, \cos \, \Theta_3 \qquad (C-13)$$

$$\omega_2 \, R_2 \, \sin \, \Theta_2 = \omega_3 \, R_3 \, \sin \, \Theta_3 \qquad (C-14)$$

Solving equation C-14 for ω_2 in terms of ω_3,

$$\omega_2 = - \, \frac{\omega_3 \, R_3 \, \sin \, \Theta_3}{R_2 \, \sin \, \Theta_2} \qquad (C-15)$$

and substituting into equation C-13,

$$V_A + \frac{R_2 \, R_3 \, \omega_3 \, \sin \, \Theta_3 \, \cos \, \Theta_2}{R_2 \, \sin \, \Theta_2} = \omega_3 \, R_3 \, \cos \, \Theta_3 \qquad (C16)$$

ω_3 can be determined as:

$$\omega_3 = \frac{V_A}{R_3 \, \cos \, \Theta_3 - \dfrac{R_3 \, \cos \, \Theta_2 \, \sin \, \Theta_3}{\sin \, \Theta_2}} \qquad (C-17)$$

Substituting ω_3 back into equation C-15, ω_2 can be determined as:

$$\omega_2 = \frac{V_A \sin \Theta_3}{R_2 (\sin \Theta_2 \cos \Theta_3 - \cos \Theta_2 \sin \Theta_3)} \qquad (C-18)$$

The angular acceleration of links R_3 and R_3 is found in the same manner. As with the angular velocities, the angular accelerations are assumed to be in the positive Z direction. The acceleration of point B equals the acceleration of point A plus the acceleration of point B with respect to point A.

$$\bar{a}_B = \bar{a}_A + \bar{a}_{B/A} \qquad (C-19)$$

Based on an initial assumption, the acceleration of point A is zero. The acceleration of point B with respect to point A has a normal and tangential component which can be determined by,

$$a_{B/A} = \alpha_2 \hat{k} \times \bar{r}_{B/A} + \omega_2 \hat{k} \times \omega_2 \hat{k} \times \bar{r}_{B/A} \qquad (C-20)$$

The vector distance $\bar{r}_{B/A}$ can be represented in terms of link R_2 and its angle.

$$\bar{r}_{B/A} = R_2 \left(- \cos \Theta_2 \hat{i} - \sin \Theta_2 \hat{j} \right) \qquad (C-21)$$

Substituting C-21 into equation C-20 and solving the cross products yields

$$\bar{a}_B = a_{B/A} = - \alpha_2 R_2 \cos \Theta_2 \hat{j} + \alpha_2 R_2 \sin \Theta_2 \hat{i} +$$

$$\omega_2^2 R_2 \cos \Theta_2 \hat{i} + \omega_2^2 R_2 \sin \Theta_2 \hat{j} \qquad (C-22)$$

The acceleration of point B also equals the sum of the acceleration of point C and the acceleration of point B with respect to point C.

$$\bar{a}_B = \bar{a}_C + \bar{a}_{B/C} \qquad (C-23)$$

The acceleration of point C is zero. The acceleration of point B with respect to point C can be solved in the same manner as equation C-19.

$$\bar{a}_B = \alpha_3 \hat{k} \times \bar{r}_{B/C} + \omega_3 \hat{k} \times \omega_3 \hat{k} \times \bar{r}_{B/C} \qquad (C-24)$$

64

The vector distance can be represented in terms of link r_3 and its angle.

$$\overline{r}_{B/C} = R_3 (\cos \Theta_3 \; \hat{i} + \sin \Theta_3 \; \hat{j}) \tag{C-25}$$

Substituting equation C-25 into equation C-24 and solving the cross products yields:

$$\overline{a}_B = \overline{a}_{B/C} = \alpha_3 R_3 \cos \Theta_3 \; \hat{j} - \alpha_3 R_3 \sin \Theta_3 \; \hat{i} -$$

$$\omega_3^2 R_3 \cos \Theta_3 \; \hat{i} - \omega_3^2 R_3 \sin \Theta_3 \; \hat{j} \tag{C-26}$$

By equating C-22 and C-26, an equation can be written for each of the $\hat{i}$ and $\hat{j}$ components,

$$\alpha_2 R_2 \sin \Theta_2 + \omega_2^2 R_2 \cos \Theta_2 = - \alpha_3 R_3 \sin \Theta_3 - \omega_3^2 R_3 \cos \Theta_3 \tag{C-27}$$

$$- \alpha_2 R_2 \cos \Theta_2 + \omega_2^2 R_2 \sin \Theta_2 = \alpha_3 R_3 \cos \Theta_3 - \omega_3^2 R_3 \sin \Theta_3 \tag{C-28}$$

The results are two equations and two unknowns. Solving equation C-27 for α_2 and reducing it yields:

$$\alpha_2 = - \; \alpha_3 \frac{R_3}{R_2} \frac{\sin \Theta_3}{\sin \Theta_2} + \omega_3^2 \frac{R_3}{R_2} \frac{\cos \Theta_3}{\sin \Theta_2} + \omega_2^2 \frac{\cos \Theta_2}{\sin \Theta_2} \tag{C-29}$$

Equation C-29 can now be substituted into equation C-28 yielding an equation for α_3

$$\alpha_3 R_3 \frac{R_2}{R_2} \frac{\cos \Theta_2}{\sin \Theta_2} \sin \Theta_3 + \omega_3^2 R_3 \frac{R_2}{R_2} \frac{\cos \Theta_2}{\sin \Theta_2} \cos \Theta_3 + \omega_2^2 R_2 \frac{\cos^2 \Theta_2}{\sin \Theta_2} +$$

$$\omega_2^2 R_2 \sin \Theta_2 = \alpha_3 R_3 \cos \Theta_3 - \omega_3^2 R_3 \sin \Theta_3 \tag{C-30}$$

$$\alpha_3 R_3 \frac{\sin \Theta_3}{\tan \Theta_2} + \omega_3^2 R_3 \frac{\cos \Theta_3}{\tan \Theta_2} + \omega_3^2 R_2 \frac{\cos \Theta_2}{\tan \Theta_2} + \omega_2^2 R_2 \sin \Theta_2 =$$

$$\alpha_3 R_3 \cos \Theta_3 - \omega_3^2 R_3 \sin \Theta_3 \tag{C-31}$$

65

$$\alpha_3 = \frac{\omega_3^2 R_3 \left(\sin \Theta_3 + \dfrac{\cos \Theta_3}{\tan \Theta_2} \right) + \omega_2^2 R_2 \left(\sin \Theta_2 + \dfrac{\cos \Theta_2}{\tan \Theta_2} \right)}{R_3 \left(\cos \Theta_3 - \dfrac{\sin \Theta_3}{\tan \Theta_2} \right)} \qquad \text{(C-32)}$$

Since α_3 is now known, α_2 can be determined using equation C-29.

$$\alpha_2 = - \left(\alpha_3 \frac{R_3}{R_2} \frac{\sin \Theta_3}{\sin \Theta_2} + \omega_3^2 \frac{R_3}{R_2} \frac{\cos \Theta_3}{\sin \Theta_2} + \omega_2^2 \frac{\cos \Theta_2}{\sin \Theta_2} \right) \qquad \text{(C-29)}$$

These quantities are used in the computer program to solve for the velocity and acceleration of any given point on the mechanism as a function of piston velocity.

Figure C-1.   Kinematic analysis model

67

FORTRAN Program

```
100=        PROGRAM KINEMAT (OUTPUT,TAPE6=OUTPUT)
110=        IMPLICIT REAL (A-Z)
120=        DIMENSION F(21,10)
130=        T3=67.84*3.1415927/180
140=        R2=3.8
150=        R3=2.387
160=        DO 30 UA=-1,-5,-1
170=        WRITE (6,100) UA
180=        WRITE (6,110)
190=  100   FORMAT (1H1,10X,"VELOCITY OF A=",F4.1,1X,"INCHES PER SECOND.")
200=  110   FORMAT (6X,"W2K",7X,"ALF2K",8X,"W3K",7X,"ALF3K")
210=        DELTS=2.0
220=        DO 20 H=1,21
230=        DO 10 I=1,500
240=        T2=ASIN((2.9+DELTS-R3*SIN(T3))/R2)
250=        T3=ACOS((3.7-R2*COS(T2))/R3)
260=  10    CONTINUE
270=        ST2=SIN(T2)
280=        ST3=SIN(T3)
290=        CT2=COS(T2)
300=        CT3=COS(T3)
310=        W3K=UA/(R3*(CT3-CT2*ST3/ST2))
320=        W2K=-W3K*R3*ST3/R2/ST2
330=        ALF3K=(R3*W3K**2.*(ST3+CT3*CT2/ST2)+R2*W2K**2.*(ST2+
340=        /CT2/ST2))/(R3*(CT3-ST3*CT2/ST2))
350=        ALF2K=-(ALF3K*R3/R2*ST3/ST2+W3K**2.*R3/R2*CT3/ST2+W2K**2.*CT2
360=        /ST2)
370=        R=.5
380=        T=T3
390=        CALL  POINT  (R,T,XI,XJ,UI,UJ,MAGU,AI,AJ,MAGA,W3K,ALF3K)
400=        F(H,1)=XI
410=        F(H,2)=XJ
420=        F(H,3)=UI
430=        F(H,4)=UJ
440=        F(H,5)=MAGU
450=        F(H,6)=AI
460=        F(H,7)=AJ
```

68

```
460=      F(H,7)=AJ
470=      F(H,8)=MAGA
480=      T3=T3+(120.-95.)/12.*3.1415927/180.
490=      WRITE (6,240) W2K,ALF2K,W3K,ALF3K
500= 240  FORMAT (1X,4(3X,F8.4))
510=      DELTS=DELTS-.1
520= 20   CONTINUE
530=      WRITE (6,70)
540= 70   FORMAT(3(/))
550= 200  FORMAT (7X,"XI",10X,"XJ", 8X, "VI",10X,"VJ", 7X, "MAGV",9X,
560=     /"AI", 9X,"AJ", 8X,"MAGA")
570= 210  FORMAT (1X,8(3X,F8.4))
580=      WRITE (6,70)
590=      WRITE (6,230)
600= 230  FORMAT (10X,"POINT F")
610=      WRITE (6,200)
620=      WRITE (6,210) ((F(I,J),J=1,8),I=1,21)
630= 30   CONTINUE
640=      STOP
650=      END
660=      SUBROUTINE POINT (R,T,XI,XJ,VI,VJ,MAGV,AI,AJ,MAGA,W3K,ALF3K)
670=      IMPLICIT REAL (A-Z)
680=      XI=-3.6+R*COS(T)
690=      XJ=R*SIN(T)
700=      VI=-W3K*R*SIN(T)
710=      VJ=W3K*R*COS(T)
720=      MAGV=(VI**2+VJ**2)**.5
730=      AI=-(ALF3K*R*SIN(T)+W3K**2*R*COS(T))
740=      AJ=ALF3K*R*COS(T)-W3K**2*R*SIN(T)
750=      MAGA=(AI**2+AJ**2)**.5
760=      RETURN
770=      END
780=*EOR
790=*EOF
```

VELOCITY OF A=-1.0 INCHES PER SECOND.

J2.	ALF2K	U3K	ALF3K
-.3250	7.9971	1.2295	-12.4757
-.5994	1.8308	.7094	-2.8326
-.4930	.8859	.5331	-1.3741
-.4308	.5432	.4359	-.8513
-.3928	.3742	.3717	-.5969
-.3659	.2762	.3247	-.4513
-.3458	.2131	.2880	-.3592
-.3302	.1696	.2582	-.2970
-.3177	.1380	.2330	-.2528
-.3076	.1140	.2111	-.2202
-.2993	.0953	.1918	-.1956
-.2923	.0803	.1743	-.1767
-.2866	.0679	.1583	-.1618
-.2817	.0576	.1435	-.1500
-.2776	.0488	.1296	-.1406
-.2742	.0412	.1164	-.1331
-.2714	.0346	.1038	-.1271
-.2691	.0287	.0917	-.1223
-.2672	.0235	.0799	-.1186
-.2657	.0187	.0683	-.1157
-.2646	.0144	.0570	-.1135

POINT F

XI	XJ	UI	UJ	MAGU	AI	AJ	MAGA
-3.3642	.4409	-.5421	.2899	.6148	5.1444	-3.6079	6.2835
-3.4051	.4605	-.3267	.1383	.3547	1.2062	-.7838	1.4385
-3.4336	.4715	-.2513	.0887	.2665	.6006	-.3627	.7016
-3.4564	.4789	-.2088	.0626	.2180	.3805	-.2133	.4362
-3.4758	.4843	-.1800	.0462	.1858	.2719	-.1410	.3063
-3.4927	.4883	-.1586	.0348	.1623	.2091	-.0999	.2317
-3.5076	.4914	-.1415	.0266	.1440	.1689	-.0740	.1844
-3.5211	.4937	-.1275	.0204	.1291	.1414	-.0563	.1522
-3.5332	.4955	-.1154	.0156	.1165	.1216	-.0438	.1293
-3.5442	.4969	-.1049	.0118	.1056	.1069	-.0344	.1123
-3.5542	.4979	-.0955	.0088	.0959	.0957	-.0273	.0995
-3.5633	.4987	-.0869	.0064	.0872	.0870	-.0216	.0896
-3.5716	.4992	-.0790	.0045	.0792	.0801	-.0171	.0819
-3.5792	.4996	-.0717	.0030	.0718	.0745	-.0134	.0757
-3.5860	.4998	-.0648	.0018	.0648	.0701	-.0104	.0708
-3.5921	.4999	-.0582	.0009	.0582	.0664	-.0078	.0669
-3.5976	.4999	-.0519	.0002	.0519	.0635	-.0057	.0638
-3.6025	.5000	-.0458	-.0002	.0458	.0612	-.0039	.0613
-3.6068	.5000	-.0399	-.0005	.0399	.0593	-.0024	.0594

63300 CM STORAGE USED.
8.578 CP SECONDS COMPILATION TIME.

XI	XJ	UI	UJ	MAGU	AI	AJ	MAGA
-3.6105	.4999	-.0342	-.0007	.0342	.0579	-.0011	.0579
-3.6136	.4999	-.0285	-.0008	.0285	.0568	-.0001	.0568

VELOCITY OF A=-2.0 INCHES PER SECOND.

.2K	ALF2K	W3K	ALF3K
-1.3519	31.9885	2.4590	-49.9027
-1.1933	7.3231	1.4189	-11.3302
-.9799	3.5438	1.0662	-5.4965
-.3617	2.1728	.8719	-3.4054
-.7856	1.4969	.7433	-2.3875
-.7318	1.1047	.6494	-1.8052
-.6916	.8525	.5761	-1.4370
-.6604	.6785	.5163	-1.1879
-.6355	.5519	.4659	-1.0111
-.6152	.4561	.4222	-.8809
-.5986	.3812	.3835	-.7825
-.5847	.3211	.3486	-.7066
-.5731	.2717	.3167	-.6471
-.5634	.2304	.2870	-.6000
-.5553	.1952	.2592	-.5625
-.5485	.1649	.2329	-.5325
-.5428	.1383	.2076	-.5085
-.5382	.1148	.1833	-.4894
-.5344	.0938	.1597	-.4744
-.5315	.0749	.1366	-.4627
-.5292	.0576	.1140	-.4540

MAGU	AI	AJ	MAGA
1.2295	20.5777	-14.4315	25.1338
.7094	4.8247	-3.1351	5.7538
.5331	2.4024	-1.4507	2.8064
.4359	1.5218	-.8530	1.7446
.3717	1.0877	-.5642	1.2253
.3247	.8363	-.3997	.9269
.2880	.6755	-.2958	.7374
.2582	.5655	-.2254	.6087
.2330	.4865	-.1751	.5171
.2111	.4278	-.1377	.4494
.1918	.3829	-.1091	.3981
.1743	.3479	-.0861	.3585
.1583	.3202	-.0684	.3274
.1435	.2980	-.0537	.3028
.1296	.2802	-.0415	.2833
.1164	.2668	-.0313	.2676
.1038	.2541	-.0228	.2552
.0917	.2448	-.0156	.2453
.0799	.2373	-.0095	.2375
.0683	.2315	-.0045	.2316
.0570	.2271	-.0003	.2271

POINT F

XI	XJ	UI	UJ
-3.3642	.4409	-1.0842	.5797
-3.4051	.4605	-.6533	.2765
-3.4336	.4715	-.5027	.1774
-3.4564	.4789	-.4176	.1252
-3.4758	.4843	-.3600	.0923
-3.4927	.4883	-.3171	.0697
-3.5076	.4917	-.2831	.0532
-3.5211	.4937	-.2549	.0408
-3.5332	.4955	-.2309	.0311
-3.5442	.4969	-.2008	.0236
-3.5542	.4979	-.1910	.0176
-3.5633	.4987	-.1738	.0128
-3.5716	.4992	-.1581	.0090
-3.5792	.4996	-.1434	.0060
-3.5860	.4998	-.1296	.0036
-3.5921	.4999	-.1164	.0018
-3.5976	.5000	-.1038	.0005
-3.6025	.5000	-.0917	-.0005
-3.6068	.5000	-.0798	-.0011
-3.6105	.4998	-.0683	-.0014
-3.6138	.4998	-.0570	-.0016

JELOCITY OF A=-3.0 INCHES PER SECOND.

VE

VE	ALF2K	U3K	ALF3K
-2.7679	71.9741	3.6885	********
-1.7981	16.4769	2.1283	-25.4930
-1.4699	7.9735	1.5993	-12.3672
-1.2925	4.8889	1.3078	-7.6621
-1.1794	3.3681	1.1150	-5.3718
-1.3977	2.4856	.9740	-4.0616
-1.2374	1.9181	.8641	-3.2332
-.9906	1.5265	.7745	-2.6728
-.9532	1.2418	.6989	-2.2749
-.9228	1.0263	.6333	-1.9821
-.8978	.8577	.5753	-1.7607
-.8770	.7225	.5229	-1.5899
-.8597	.6114	.4750	-1.4561
-.8451	.5184	.4306	-1.3501
-.8329	.4393	.3888	-1.2656
-.8227	.3710	.3493	-1.1981
-.8143	.3112	.3115	-1.1441
-.8073	.2583	.2750	-1.1011
-.8017	.2111	.2396	-1.0673
-.7972	.1684	.2050	-1.0412
-.7938	.1297	.1710	-1.0215

POINT F

XI	XJ	UI	UJ	MAGU	AI	AJ	MAGA
-3.3642	.4409	-1.6264	.8696	1.8443	46.2999	-32.4708	56.5511
-3.4051	.4605	-.9800	.4148	1.0641	10.8556	-7.0540	12.9461
-3.4336	.4715	-.7540	.2662	.7996	5.4054	-3.2641	6.3145
-3.4564	.4789	-.6264	.1878	.6539	3.4241	-1.9193	3.9254
-3.4758	.4843	-.5400	.1385	.5575	2.4473	-1.2694	2.7569
-3.4927	.4883	-.4757	.1045	.4870	1.8816	-.8993	2.0855
-3.5076	.4914	-.4246	.0798	.4321	1.5198	-.6656	1.6592
-3.5211	.4937	-.3824	.0611	.3872	1.2723	-.5071	1.3697
-3.5332	.4955	-.3463	.0467	.3494	1.0946	-.3940	1.1634
-3.5442	.4970	-.3147	.0353	.3167	.9625	-.3099	1.0111
-3.5542	.4980	-.2864	.0263	.2876	.8615	-.2454	.8958
-3.5633	.4987	-.2608	.0192	.2615	.7828	-.1947	.8066
-3.5716	.4992	-.2371	.0135	.2375	.7205	-.1540	.7367
-3.5792	.4996	-.2151	.0090	.2153	.6706	-.1208	.6814
-3.5863	.4998	-.1945	.0055	.1944	.6305	-.0933	.6373
-3.5921	.4999	-.1746	.0028	.1746	.5980	-.0704	.6021
-3.5976	.5000	-.1557	.0007	.1557	.5718	-.0512	.5741
-3.6025	.5000	-.1375	-.0007	.1376	.5507	-.0350	.5519
-3.6325	.5000	-.1198	-.0016	.1198	.5340	-.0214	.5344
-3.6105	.4999	-.1025	-.0022	.1025	.5209	-.0101	.5210
-3.6136	.48C0	-.0855	-.0023	.0855	.5110	-.0007	.5110

VELOCITY OF A=4.0 INCHES PER SECOND.

W2K	ALF2K	W3K	ALF3K
-3.7039	127.9540	4.9180	xxxxxxx
-2.3975	29.2923	2.8377	-45.3208
-1.9598	14.1751	2.1324	-21.9861
-1.7234	8.6913	1.7438	-13.6216
-1.5712	5.9878	1.4867	-9.5499
-1.4636	4.4188	1.2987	-7.2206
-1.3832	3.4100	1.1522	-5.7480
-1.3208	2.7138	1.0327	-4.7517
-1.2709	2.2076	.9318	-4.0443
-1.2304	1.8245	.8444	-3.5237
-1.1971	1.5249	.7670	-3.1301
-1.1694	1.2844	.6973	-2.8264
-1.1462	1.0869	.6334	-2.5885
-1.1268	.9216	.5741	-2.4002
-1.1106	.7810	.5185	-2.2500
-1.0970	.6595	.4657	-2.1299
-1.0857	.5533	.4153	-2.0339
-1.0764	.4593	.3666	-1.9576
-1.0689	.3752	.3194	-1.8975
-1.0630	.2994	.2733	-1.8510
-1.0585	.2305	.2280	-1.8160

POINT F

XI	XJ	VI	UJ	MAGU	AI	AJ	MAGA
-3.3642	.4409	-2.1685	1.1595	2.4590	82.3109	-57.7258	100.5354
-3.4051	.4605	-1.3066	.5530	1.4189	19.2988	-12.5404	23.0153
-3.4336	.4715	-1.0054	.3549	1.0662	9.6095	-5.8029	11.2257
-3.4564	.4789	-.8352	.2504	.8719	6.0874	-3.4121	6.9784
-3.4758	.4843	-.7200	.1847	.7433	4.3507	-2.2567	4.9012
-3.4927	.4883	-.6342	.1394	.6494	3.3451	-1.5987	3.7075
-3.5076	.4914	-.5662	.1064	.5761	2.7019	-1.1832	2.9496
-3.5211	.4937	-.5099	.0815	.5163	2.2619	-.9016	2.4350
-3.5332	.4955	-.4617	.0622	.4659	1.9460	-.7004	2.0682
-3.5442	.4969	-.4106	.0471	.4222	1.7111	-.5509	1.7976
-3.5542	.4979	-.3819	.0351	.3835	1.5315	-.4362	1.5925
-3.5633	.4987	-.3477	.0256	.3486	1.3916	-.3481	1.4340
-3.5716	.4992	-.3162	.0180	.3167	1.2808	-.2737	1.3097
-3.5792	.4996	-.2868	.0120	.2870	1.1922	-.2147	1.2114
-3.5860	.4998	-.2591	.0073	.2592	1.1208	-.1650	1.1330
-3.5921	.4999	-.2328	.0037	.2328	1.0631	-.1252	1.0705
-3.5976	.5000	-.2076	.0010	.2076	1.0165	-.0910	1.0206
-3.6025	.5000	-.1833	-.0009	.1833	.9791	-.0623	.9811
-3.6068	.5000	-.1597	-.0022	.1597	.9493	-.0381	.9501
-3.6105	.4999	-.1366	-.0029	.1366	.9261	-.0179	.9262
-3.6138	.4998	-.1139	-.0031	.1140	.9084	-.0012	.9084

73

VELOCITY OF A--5.0 INCHES PER SECOND.

W2K	ALF2K	W3K	ALF3K
-4.6298	199.9282	6.1476	*******
-2.9959	45.7693	3.5471	-70.8138
-2.4498	22.1486	2.6655	-34.3534
-1.1542	13.5802	2.1797	-21.2837
-1.9640	9.3559	1.8584	-14.9217
-1.8296	6.9044	1.6234	-11.2822
-1.7290	5.3282	1.4402	-8.9812
-1.6509	4.2404	1.2908	-7.4246
-1.5887	3.4494	1.1648	-6.3192
-1.5381	2.8507	1.0555	-5.5058
-1.4964	2.3826	.9588	-4.8908
-1.4617	2.0068	.8716	-4.4163
-1.4328	1.6983	.7917	-4.0446
-1.4085	1.4400	.7176	-3.7503
-1.3882	1.2203	.6481	-3.5157
-1.3712	1.0305	.5822	-3.3280
-1.3571	.8645	.5191	-3.1780
-1.3455	.7176	.4583	-3.0587
-1.3361	.5863	.3993	-2.9648
-1.3287	.4679	.3416	-2.8921
-1.3231	.3602	.2849	-2.8375

POINT F

XI	XJ	UI	UJ	MAGU	AI	AJ	MAGA
-3.3642	.4409	-2.7106	1.4494	3.0738	128.6108	-90.1966	157.0865
-3.4051	.4605	-1.6333	.6913	1.7736	30.1544	-19.5943	35.9614
-3.4336	.4715	-1.2567	.4436	1.3327	15.0149	-9.0671	17.5402
-3.4564	.4789	-1.0440	.3130	1.0899	9.5115	-5.3314	10.9038
-3.4758	.4843	-.9001	.2308	.9292	6.7980	-3.5261	7.6581
-3.4927	.4883	-.7928	.1742	.8117	5.2267	-2.4980	5.7930
-3.5076	.4914	-.7077	.1330	.7201	4.2218	-1.8488	4.6088
-3.5211	.4937	-.6373	.1019	.6454	3.5342	-1.4087	3.8046
-3.5332	.4955	-.5772	.0778	.5824	3.0407	-1.0944	3.2316
-3.5442	.4969	-.5245	.0589	.5278	2.6735	-.8608	2.8087
-3.5542	.4979	-.4774	.0439	.4794	2.3930	-.6816	2.4882
-3.5633	.4987	-.4346	.0320	.4358	2.1743	-.5407	2.2406
-3.5716	.4992	-.3952	.0225	.3959	2.0013	-.4277	2.0464
-3.5792	.4996	-.3585	.0150	.3588	1.8628	-.3354	1.8927
-3.5860	.4998	-.3239	.0091	.3240	1.7513	-.2592	1.7703
-3.5921	.4999	-.2910	.0046	.2911	1.6611	-.1956	1.6726
-3.5976	.5000	-.2595	.0012	.2595	1.5883	-.1423	1.5947
-3.6025	.5000	-.2291	-.0012	.2291	1.5299	-.0973	1.5330
-3.6068	.5000	-.1996	-.0027	.1996	1.4833	-.0595	1.4845
-3.6105	.4999	-.1708	-.0036	.1708	1.4470	-.0280	1.4472
-3.6138	.4998	-.1424	-.0030	.1425	1.4193	.0010	1.4193

APPENDIX D

DRAWINGS

APPLICATION			REVISIONS		
NEXT ASSY	USED ON	SYM	DESCRIPTION	DATE	APPROVAL
83F470					

CYLINDER:

1 5/8 BORE — 2 STROKE

PART NO. F-221-X

SOURCE

FABCO - AIR INC.
3716 NE 49TH ROAD
GAINESVILLE, FLORIDA 32601

SOURCE CONTROL DWG.

PART NO. 83A471

ORIGINAL DATE OF DRAWING		U S ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
09-30-83		DOVER, NEW JERSEY 07801
DRAFTSMAN	CHECKER	
ENGR	ENGR	CYLINDER, HYDRAULIC
ENGR	ENGR	

		SIZE	CODE IDENT NO.	
		A	19200	83A471
		SCALE	UNIT WT	SHEET

ARRADCOM FORM 65 JUN 78 REPLACES SARPA FORM 1038 OCT 75 WHICH IS OBSOLETE

Figure D-1. Hydraulic cylinder

83F470

SCREW, SOCKET HEAD CAP

.190 (NO.10) 32 UNF-2H X 4 1/2 LG.

SOURCE

FABCO - AIR INC.
3716 NE 49TH ROAD
GAINESVILLE, FLORIDA 32601

SOURCE CONTROL DRAWING
PART NO. 83A477

ORIGINAL DATE OF DRAWING 83-10-27		U S ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND DOVER, NEW JERSEY 07801			
DRAFTSMAN	CHECKER	SCREW, SOCKETHEAD CAP			
ENGR	ENGR				
ENGR	ENGR				
		SIZE A	CODE IDENT NO. 19200	83A477	
		SCALE	UNIT WT		SHEET

Figure D-2.   Socket head cap screw

.02 +.01 X 45°±1°
CHAMBER BOTH ENDS
.003 R MAX
2 PLACES

DETAIL A

Ø DIM. C
-A-

DIM. D
⌀ .0015 A
2 PLACES

.029±.003
2 PLACES

63√

SEE DETAIL A

DIM. B

.160 ±.005

DIM. A

Ⓐ

DIM.A	DIM.B	DIM.C	DIM. D	P/N
1.36-.01	1.060-.005	.310-.001	.290-.002	-1
2.35-.01	2.060-.005	.248-.001	.2300-.0015	-2
1.36-.01	1.060-.005	.248-.001	.2300-.0015	-3

NOTES:
1. ANSI Y14.5M-1982 APPLIES.
2. FINISH 125√ ALL OVER, EXCEPT AS NOTED.
3. MATERIAL: STEEL, 4340 ANSI PER FED-STD-66 OR EQUAL.
4. HEAT TREAT TO HARDNESS, ROCKWELL C28-32.
5. PROTECTIVE FINISH: FINISH 3.3.1 OF MIL-STD-171.

PART NO. SEE TABLE

U S ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
DOVER, NEW JERSEY 07801

PIN

ORIGINAL DATE OF DRAWING	10-12-83
DRAFTSMAN	CHECKER
ENGR	ENGR
ENGR	ENGR

DO NOT SCALE DRAWING
UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON DECIMALS ±
FRACTIONS ±   ANGLES ±

MECHANICAL PROPERTIES
YP
TS
EL2
RA
BH
RH

SIZE C | CODE IDENT NO. 19200 | 83C465
SCALE 2/1 | UNIT WT. | SHEET

83F470
NEXT ASSY | USED ON
APPLICATION

Figure D-3. Pin, part number 83C465

Figure D-4. Yoke connector, part number 83C466

81

NOTES:
1. SPEC ANSI Y14.5M1982 APPLIES.
2. FINISH 125√ EXCEPT AS NOTED.
3. MATERIAL: STEEL PLATE ALLOY
   GRADE E,F,G,H,L,M,P, OR Q SPEC ASTM A514.
4. HEAT TREAT AND QUENCH TO HARDNESS, RC 28-32.
5. PROTECTIVE FINISH: FINISH 3.3.1. OF MIL-STD-171.
6. BREAK SHARP CORNER .01 MIN.
7. BREAK ALL SHARP CORNERS WITH .01 X .01 X 45°±1°
   CHAMFER AND/OR .01 RADIUS.

Figure D-5. Finger, part number 83D467

83

Figure D-6. Yoke, part number 83D464

85

NOTES:
1. ANSI Y145M-1982 APPLIES.
2. MATERIAL: STEEL, PLATE,
   ALLOY GRADE E,F,G,H,L,M,P, OR
   Q OF SPEC ASTM A514.
3. FINISH 125/ ALL OVER.

.03+.01 X 45° ±1°
CHAMFER

.380-.002

//|.002|A

2.860-.005

2.375-.005

-A-

R

R

PART NO. 83C472

Figure D-7. End post, part number 83C472

Figure D-8. Center post, part number 83D475

89

Figure D-9. Mounting plate, part number 83D476

Figure D-10. Saddle, part number 83D468

Figure D-11. Saddle assembly (machining), part number 83F474

95

Figure D-12. Saddle assembly (weldment), part number 83F473

97

Figure D-13. Gripper assembly, part number 83F470

Commander
Armament Research and Development Center
U.S. Army Armament, Munitions and Chemical Command
ATTN: SMCAR-TSS (5)
        SMCAR-LC
        SMCAR-LCB
        SMCAR-LCE
        SMCAR-LCM
        SMCAR-LCN
        SMCAR-LCS
        SMCAR-LCU
        SMCAR-LCW (10)
Dover, NJ   07801-5001

Commander
U.S. Army Armament, Munitions and Chemical Command
ATTN: AMSMC-GCL(D)
Dover, NJ   07801-5001

Administrator
Defense Technical Information Center
ATTN: Accessions Division (12)
Cameron Station
Alexandria, VA   22314

Director
U.S. Army Materiel Systems Analysis Activity
ATTN: DRXSY-MP
Aberdeen Proving Ground, MD   21005-5066

Commander
Chemical Research and Development Center
U.S. Army Armament, Munitions and Chemical Command
ATTN: SMCCR-SPS-IL
Aberdeen Proving Ground, MD   21010-5423

Commander
Chemical Research and Development Center
U.S. Army Armament, Munitions and Chemical Command
ATTN: SMCCR-RSP-A
Aberdeen Proving Ground, MD   21010-5423

Director
Ballistic Research Laboratory
ATTN: AMXBR-OD-ST
Aberdeen Proving Ground, MD   21005-5066

Chief
Benet Weapons Laboratory, LCWSL
Armament Research and Development Center
U.S. Army Armament, Munitions and Chemical Command
ATTN: SMCAR-LCB-TL
Watervliet, NY 12189-5000

Commander
U.S. Army Armament, Munitions and Chemical Command
ATTN: AMSMC-LEP-L
Rock Island, IL 61299-6000

Director
U.S. Army TRADOC Systems Analysis Activity
ATTN: ATAA-SL
White Sands Missile Range, NM 88002

Assistant Secretary of the Army
Research and Development
ATTN: Department for Science and Technology
The Pentagon
Washington, DC 20315

Commander
U.S. Army Materiel Command
ATTN: AMC-SG
5001 Eisenhower Avenue
Alexandria, VA 22304

Commander
U.S. Army Electronics Command
ATTN: Technical Library
Ft. Monmouth, NJ 07703

Commander
U.S. Army Mobility Equipment Research and Development Command
ATTN: Technical Library
Ft. Belvoir, VA 22060

Commander
U.S. Army Tank-Automotive Research and Development Command
ATTN: Tech Library - DRSTA-TSL
Warren, MI 48090

Commander
U.S. Military Academy
ATTN: CHMN, Mechanical Engineer Dept.
West Point, NY 10996

Commander
U.S. Army Missile Command
ATTN: Documents Section, Bldg 4484
Redstone Arsenal, AL 35898

Commander
Rock Island Arsenal
ATTN: SMCRI-ENM (Mat Sci Div)
Rock Island, IL 61299

Commander
HQ, U.S. Army Aviation School
ATTN: Office of the Librarian
Ft. Rucker, AL 36362

Commander
U.S. Army Foreign Science and Technology Center
ATTN: DRXST-SD
220 7th Street, N.E.
Charlottesville, VA 22901

Commander
U.S. Army Materials and Mechanics Research Center
ATTN: Technical Library, DRXMR-PL (2)
Watertown, MA 02172

Commander
U.S. Army Research Office
ATTN: Chief IPO
P.O. Box 12211
Research Triangle Park, NC 27709

Commander
Harry Diamond Laboratories
ATTN: Technical Library
2800 Powder Mill Road
Adelphia, MD 20783

Director
U.S. Naval Research Laboratory
ATTN: Director, Mech Div
       Code 26-27 (DOC Library)
Washington, DC 20375

Mechanical Properties Data Center
Battelle Columbus Laboratory
505 King Avenue
Columbus, OH 43201

Commander
Naval Surface Weapons Center
ATTN: Technical Library
       Code X212
Dahlgren, VA 22448